

Epson FX-890II dot matrix printer 240 x 144 DPI 612 cps

Brand : Epson

Product code: C11CF37401

Product name : FX-890II

- Market-leading print speeds: Complete high-volume print runs even faster
 - Very low TCO: Cheap, long-lasting consumables and low power use
 - Even better reliability: Improved by 25% to 25,000 power-on hours
 - Smaller footprint: Allows for easy placement within a business environment
 - Energy Star compliant: To ensure the best possible energy efficiency
- 240 x 144 DPI, 9 pins, 80 columns, USB, parallel, AC 198-264 V, 414 x 320 x 177 mm
 Epson FX-890II. Maximum print speed: 612 cps, Maximum resolution: 240 x 144 DPI, Maximum print speed (draft): 463 cps. Maximum print size: A4 (210 x 297 mm), Paper tray media types: Envelopes, Cut sheet thickness range: 0.12 - 0.46 mm. Product colour: Black, Buffer size: 128 KB, Sound pressure level (printing): 55 dB. Standard interfaces: Parallel, USB 2.0. Print head: 9-pin, Print direction: Bidirectional, Print head life: 400 million characters



Printing		Power	
Maximum resolution *	240 x 144 DPI	Power consumption (economy mode)	0.5 W
Maximum printing width (columns) *	80	Operational conditions	
Colour *	✗	Operating temperature (T-T)	5 - 35 °C
Maximum print speed *	612 cps	Storage temperature (T-T)	-30 - 60 °C
Maximum print speed (draft)	463 cps	Operating relative humidity (H-H)	10 - 80%
Character pitch	10 cpi	Storage relative humidity (H-H)	30 - 60%
Maximum number of copies	6 copies	Weight & dimensions	
Built-in barcodes	CODABAR (NW-7), Code 128 (A/B/C), Code 39, Industrial 2/5, Matrix 2/5, POSTNET, UPC-A, UPC-E	Width	414 mm
Bitmap fonts	Draft, OCR-B, Roman, Sans Serif	Depth	375 mm
Character sets	PCAPTEC, PC437, PC720, PC850, PC858, ISO 8859-15, Roman 8, Italic	Height	177 mm
Print speed	NLQ: 10 cpi: 115 chars/s, Draft: 10 cpi: 463 chars/s, HighSpeed-Draft: 10 cpi: 612 chars/s	Weight	7.2 kg
Number of characters	42	Packaging data	
Paper handling		Quantity per pack	1 pc(s)
Maximum print size	A4 (210 x 297 mm)	Package width	450 mm
Paper tray media types	Envelopes	Package depth	540 mm
Cut sheet thickness range	0.12 - 0.46 mm	Package height	280 mm
Continuous paper thickness range	0.46 - 0.46 mm	Package weight	8.91 kg
Label thickness range	0.46 - 0.46 mm	Other features	
Multi-part paper thickness range	0.12 - 0.46 mm	Standard media sizes	Sheet Paper (single- and multi-layer), Continuous Paper (single- and multi-layer), Envelopes, Cardboard
Single sheet thickness range	0.06 - 0.14 mm	Connectivity technology	Wired
Features		Print technology	Dot matrix
Product colour *	Black	Needles	18 Needles (2 x 9)
Buffer size *	128 KB	Technical details	
Sound pressure level (printing) *	55 dB	Sustainability certificates	ENERGY STAR
Page description languages *	ESC P, IBM PPDS		
Country of origin	Indonesia		

Ports & interfaces		Logistics data	
Standard interfaces *	Parallel, USB 2.0	Products per pallet	14 pc(s)
Endurance		Pallet gross weight	0 g
Print head *	9-pin	Pallet gross length	120 cm
Print direction	Bidirectional	Pallet gross width	80 cm
Print head life	400 million characters	Pallet gross height	3.09 m
Ribbon life	7.5 million characters	Products per pallet layer	2 pc(s)
Print yield	7500000 characters	Products per pallet layer (UK)	4 pc(s)
Mean time between failures (MTBF)	25000 h	Products per pallet (UK)	28 pc(s)
Power		Pallet weight (UK)	0 g
Power consumption (typical)	54 W	Pallet length (UK)	120 cm
Power consumption (standby)	8 W	Pallet width (UK)	100 cm
AC input voltage	198-264 V	Pallet height (UK)	3.09 m
		Harmonized System (HS) code	84433210



8715946634487

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 01-MAR-2025. Prints or copies of Information are only valid on the printed Publication date