Canon

Canon imageFORMULA DR-M160II Arkkisyöttöskanneri 600 x 600 DPI A4 musta

Tuotemerkki: Canon Tuoteperhe: imageFORMULA Tuotekoodi: 9725B003

Tuotteen nimi: DR-M160II

Canon imageFORMULA DR-M160II. Skannauksen enimmäiskoko: 216 x 3000 mm, Optinen skannauserottelutarkkuus: 600 x 600 DPI, Lähdön värisyvyys: 24 bittiä. Skannerityyppi: Arkkisyöttöskanneri, Tuotteen väri: musta. Anturin tyyppi: CMOS CIS, Päivittäinen käyttöjakso (maks.): 7000 sivua, Valonlähde: RGB LED. Vakiosyöttökapasiteetti (arkkia): 60 arkkia. Suurin ISO A-luokan paperikoko: A4





Scanning		Ports & interfaces	
Maximum scan size *	216 x 3000 mm	USB port *	✓
Optical scanning resolution *	600 x 600 DPI	USB version	2.0
Colour scanning	1	Standard interfaces	USB 2.0
Duplex scanning *	1	Power	
Output colour depth	24 bit	Power supply type *	AC
Output greyscale depth	8 bit	Power consumption (typical)	27 W
Film scanning	×	Power consumption (standby)	1.8 W
Greyscale levels	256	Power consumption (off)	0.5 W
ADF scan speed (b/w, A4)	60 ppm	AC input frequency	50 - 60 Hz
ADF scan speed (colour, A4)	60 ppm	Input voltage	100-240 V
Duplex ADF scan speed (b/w, A4) Duplex ADF scan speed (colour, A4)	120 ipm	Weight & dimensions	
Black/white scanning colour modes	•	Width	280 mm
J	Grayscale	Depth	606 mm
Design		Height	366.4 mm
Scanner type *	Sheet-fed scanner	Weight	3.2 kg
Product colour *	Black	Packaging content	
Built-in display *	×	Drivers included	1
Performance		Drivers included	CapturePerfect CaptureOnTouch
Sensor type * Light source Daily duty cycle (max) *	CMOS CIS RGB LED	Bundled software	eCopy PDF Pro Office Kofax VRS (with AIPE) Plug-in: EMC Captiva Cloud Runtime Controls
Scan drivers	7000 pages ISIS, TWAIN	Sustainability	
Input capacity	·	Sustainability certificates	ENERGY STAR
Standard input capacity	60 sheets	System requirements	
Paper handling		Windows operating systems supported	✓
Maximum ISO A-series paper size *	A4	Mac operating systems supported	✓
		Other features	
		Compliance certificates	RoHS
		Logistics data	

