



APC Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 11.0kW, 230V, (21) C13 & (3) C19

Brand : APC

Product code: AP8681

Product name : Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 11.0kW, 230V, (21) C13 & (3) C19

Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 11.0kW, 230V, (21) C13 & (3) C19
 APC Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 11.0kW, 230V, (21) C13 & (3) C19. PDU types: Metered, Metered-by-outlet, Switched, Rack capacity: 0U, Mounting: Vertical. AC outlets quantity: 24 AC outlet(s), AC outlet types: C13 coupler, C19 coupler. Cable length: 1.83 m. Monitoring: Current, Power, Voltage, Outlet control: Lock-out, Recycle, Turn off, Turn on. Nominal input voltage: 400 V, Maximum current: 16 A, AC input frequency: 50 - 60 Hz



| | | | |
|--------------------------------------|--------------------------------------|-------------------------------------|---|
| Design | | Certificates | |
| PDU types * | Metered, Metered-by-outlet, Switched | Compliance certificates | RoHS |
| Rack capacity * | 0U | Certification | EN 55022 A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC 15 A, ICES-003, UL, VDE |
| Mounting | Vertical | Operational conditions | |
| Product colour | Black | Operating temperature (T-T) | -5 - 45 °C |
| Ports & interfaces | | Operating relative humidity (H-H) | 5 - 95% |
| AC outlets quantity * | 24 AC outlet(s) | Storage relative humidity (H-H) | 5 - 95% |
| AC outlet types * | C13 coupler, C19 coupler | Operating altitude | 0 - 3000 m |
| Features | | Non-operating altitude | 0 - 15000 m |
| Cable length | 1.83 m | Weight & dimensions | |
| Management features | | Width | 56 mm |
| Monitoring | Current, Power, Voltage | Depth | 51 mm |
| Outlet control | Lock-out, Recycle, Turn off, Turn on | Height | 1829 mm |
| Power | | Weight | 8.23 kg |
| Nominal input voltage * | 400 V | Packaging data | |
| AC input frequency | 50 - 60 Hz | Package weight | 10.5 kg |
| Maximum current * | 16 A | Package width | 162 mm |
| Nominal output voltage | 230 V | Package depth | 117 mm |
| Load capacity | 11040 VA | Package height | 2038 mm |
| Maximum input current per phase | 16 A | Logistics data | |
| Maximum total current draw per phase | 16 A | Total carbon footprint (kg of CO2e) | 10364.02 |
| Maximum power | 11040 W | | |



0731304299530



731304299530



7313042995306

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.