



APC Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 20A/208V, 16A/230V, (21) C13 & (3) C19

Brand : APC

Product code: AP8659

Product name : Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 20A/208V, 16A/230V, (21) C13 & (3) C19

Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 20A/208V, 16A/230V, (21) C13 & (3) C19
 APC Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 20A/208V, 16A/230V, (21) C13 & (3) C19.
 PDU types: Metered, Metered-by-outlet, Switched, Rack capacity: 0U, Mounting: Vertical. AC outlets quantity: 24 AC outlet(s), AC outlet types: C13 coupler, C19 coupler. Monitoring: Current, Power, Voltage, Outlet control: Lock-out, Recycle, Turn off, Turn on. Nominal input voltage: 200-230 V, Maximum current: 16 A, AC input frequency: 50 - 60 Hz. Compliance certificates: RoHS, Certification: EN 55022 A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC 15 A, ICES-003, PSE, UL, VCCI A, VDE



Design		Certificates	
PDU types *	Metered, Metered-by-outlet, Switched	Certification	EN 55022 A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC 15 A, ICES-003, PSE, UL, VCCI A, VDE
Rack capacity *	0U	Operational conditions	
Mounting	Vertical	Operating temperature (T-T)	-5 - 45 °C
Product colour	Black	Storage temperature (T-T)	-25 - 65 °C
Ports & interfaces		Operating relative humidity (H-H)	5 - 95%
AC outlets quantity *	24 AC outlet(s)	Storage relative humidity (H-H)	5 - 95%
AC outlet types *	C13 coupler, C19 coupler	Operating altitude	0 - 3000 m
Management features		Non-operating altitude	0 - 15000 m
Monitoring	Current, Power, Voltage	Weight & dimensions	
Outlet control	Lock-out, Recycle, Turn off, Turn on	Width	56 mm
Power		Depth	51 mm
Nominal input voltage *	200-230 V	Height	1829 mm
AC input frequency	50 - 60 Hz	Weight	6.09 kg
Maximum current *	16 A	Packaging data	
Nominal output voltage	200-230 V	Package weight	8.36 kg
Load capacity	3680 VA	Package width	162 mm
Maximum input current per phase	16 A	Package depth	117 mm
Maximum total current draw per phase	16 A	Package height	2038 mm
Maximum power	3680 W	Logistics data	
Certificates		Total carbon footprint (kg of CO2e)	537.26
Compliance certificates	RoHS		



0731304299509



731304299509

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.