

## APC Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 32A, 230V, (21) C13 & (3) C19


Brand : APC Product code: AP8653

**Product name :** Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 32A, 230V, (21) C13 & (3) C19

Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 32A, 230V, (21) C13 & (3) C19
APC Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 32A, 230V, (21) C13 & (3) C19. PDU types:
Metered, Metered-by-outlet, Switched, Rack capacity: 0U, Type: Single-phase. AC outlets quantity: 24 AC outlet(s), AC outlet types: C13 coupler, C19 coupler, Power plug: IEC309. Cable length: 3 m. Monitoring:
Current, Power, Voltage, Outlet control: Lock-out, Recycle, Turn off, Turn on. Nominal input voltage: 230
V, Maximum current: 32 A, AC input frequency: 50 - 60 Hz



Design		Certificates	
PDU types * Sw	Metered, Metered-by-outlet, Switched Single-phase OU Vertical Black	Compliance certificates Certification	RoHS EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3, VDE
Rack capacity *		Operational conditions	
Mounting Product colour		Operating temperature (T-T) Storage temperature (T-T)	-5 - 45 °C -25 - 65 °C
Ports & interfaces		Operating relative humidity (H-H)	5 - 95%
AC outlets quantity * Power plug AC outlet types *	24 AC outlet(s) IEC309 C13 coupler, C19 coupler	Storage relative humidity (H-H) Operating altitude Non-operating altitude	5 - 95% 0 - 3000 m 0 - 15000 m
Features		Weight & dimensions	
Cable length	3 m	Width	56 mm
Management features		Depth	51 mm
Monitoring Outlet control	Current, Power, Voltage Lock-out, Recycle, Turn off, Turn on	Height Weight	1829 mm 8.23 kg
Power		Packaging data	
Nominal input voltage * AC input frequency Maximum current * Nominal output voltage	230 V 50 - 60 Hz 32 A 230 V	Package weight Package width Package depth Package height	10.5 kg 162 mm 118 mm 2038 mm
Load capacity	7680 VA	Logistics data	
Maximum input current per phase	32 A	Total carbon footprint (kg of CO2e)	8595.81
Maximum total current draw per phase	32 A		
Power protection features	Overload		
Maximum power	7680 W		





731304276982

0731304276982

## **Catalog Object Cloud**



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.