



## APC Rack PDU 2G, Metered-by-Outlet, ZeroU, 11.0kW, 230V, (21) C13 & (3) C19

**Brand :** APC

**Product code:** AP8481

**Product name :** Rack PDU 2G, Metered-by-Outlet, ZeroU, 11.0kW, 230V, (21) C13 & (3) C19

Rack PDU 2G, Metered-by-Outlet, ZeroU, 11.0kW, 230V, (21) C13 & (3) C19

APC Rack PDU 2G, Metered-by-Outlet, ZeroU, 11.0kW, 230V, (21) C13 & (3) C19:

APC Metered by Outlet Rack Power Distribution Units (PDUs) provide individual outlet power metering to enable energy optimization and circuit protection. Current metering provides real-time remote monitoring of connected loads. Metered by Outlet Rack PDUs provide power utilization data to allow Data Center Managers to make informed decisions on load balancing and right sizing IT environments to lower total cost of ownership. Metered by Outlet Rack PDUs include real power monitoring, a temperature/humidity sensor port, locking IEC receptacles, and ultra low profile circuit breakers. Users can access and configure Metered by Outlet Rack PDUs through secure Web, SNMP, or Telnet Interfaces which are complimented by APC Centralized Management platforms using InfraStruxure Central, Operations, Capacity, and Energy Efficiency.



Design		Certificates	
PDU types *	Metered, Metered-by-outlet	Compliance certificates	RoHS
Rack capacity *	0U	Certification	EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC Part 15 Class A, ICES-003, UL, VDE, REACH
Mounting	Vertical		
Product colour	Black		
Ports & interfaces		Operational conditions	
AC outlets quantity *	24 AC outlet(s)	Operating temperature (T-T)	-5 - 45 °C
Power plug	IEC309	Storage temperature (T-T)	-25 - 65 °C
AC outlet types *	C13 coupler, C19 coupler	Operating relative humidity (H-H)	5 - 95%
Input connection type	IEC 309 16A 3P+N+PE, IEC 309 20A 3P+N+E	Storage relative humidity (H-H)	5 - 95%
Output connections	21 x C13 & 3 x C19	Operating altitude	0 - 15000 m
Features		Weight & dimensions	
LED indicators	✓	Width	56 mm
Cable length	1.83 m	Depth	51 mm
Management features		Height	1829 mm
Monitoring	Current, Power, Voltage	Weight	8.21 kg
Management platform	Web, SNMP, Telnet	Packaging data	
Power		Package weight	10.5 kg
Nominal input voltage *	400 V	Package width	163 mm
AC input frequency	50 - 60 Hz	Package depth	117 mm
Nominal output voltage	230 V	Package height	2037 mm
Load capacity	11040 VA	Logistics data	
Maximum input current per phase	16 A	Total carbon footprint (kg of CO2e)	7251.82
Maximum total current draw per phase	16 A		
Maximum power	11040 W		



0731304317609



731304317609

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.