



APC NetShelter Basic Rack PDU, 1U, 1PH, 3.7kW 230V 16A or 3.3kW 208V 16A, x12 C13 outlets, C20 cord

Brand : APC

Product code: AP9565

Product name : NetShelter Basic Rack PDU, 1U, 1PH, 3.7kW 230V 16A or 3.3kW 208V 16A, x12 C13 outlets, C20 cord



NetShelter Basic Rack PDU, 1U, 1PH, 3.7kW 230V 16A or 3.3kW 208V 16A, x12 C13 outlets, C20 cord

APC NetShelter Basic Rack PDU, 1U, 1PH, 3.7kW 230V 16A or 3.3kW 208V 16A, x12 C13 outlets, C20 cord:

Reliable rack power distribution designed to increase manageability and efficiency in the data center The output and input connections are (12)C13 Real-time remote monitoring of connected loads User-defined alarms warn IT and data center managers of potential circuit overloads to prevent accidental power loss to critical equipment.



APC NetShelter Basic Rack PDU, 1U, 1PH, 3.7kW 230V 16A or 3.3kW 208V 16A, x12 C13 outlets, C20 cord. PDU types: Basic, Rack capacity: 0U/1U, Type: Single-phase. AC outlets quantity: 12 AC outlet(s), AC outlet types: C13 coupler, Power plug: C20 coupler. Cable length: 2.5 m. Load capacity: 3680 VA, Maximum input current per phase: 16 A, Maximum power: 3680 W. Certification: cUL Listed,CE,CSA,GOST,Queensland Australia,UL 60950,UL Listed,VDE

Design		Certificates	
PDU types *	Basic	Certification	cUL Listed,CE,CSA,GOST,Queensland Australia,UL 60950,UL Listed,VDE
Type	Single-phase		
Rack capacity *	0U/1U		
Mounting	Horizontal/Vertical	Operational conditions	
Product colour	Black	Operating temperature (T-T)	0 - 45 °C
Ports & interfaces		Storage temperature (T-T)	-25 - 65 °C
AC outlets quantity *	12 AC outlet(s)	Operating relative humidity (H-H)	0 - 95%
Power plug	C20 coupler	Storage relative humidity (H-H)	0 - 95%
AC outlet types *	C13 coupler	Weight & dimensions	
Input connection type	IEC-320 C20	Width	447 mm
Output connections	(12) IEC 320 C13	Depth	57.2 mm
Features		Height	44.5 mm
Cable length	2.5 m	Weight	2.05 kg
Power		Packaging data	
Load capacity	3680 VA	Package weight	3.64 kg
Maximum input current per phase	16 A	Package width	464 mm
Maximum power	3680 W	Package depth	229 mm
		Package height	70 mm
		Logistics data	
		Total carbon footprint (kg of CO2e)	55.19



0731304213055



731304213055

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.