

TP-Link Archer MR200 wireless router Fast Ethernet Dual-band (2.4 GHz / 5 GHz) 4G Black

Brand : TP-Link

Product code: ARCHER MR200 V2

Product name : Archer MR200

3x 10/100Mbps LAN, 1x 10/100Mbps LAN/WAN, 1x SIM Card, 3G/4G, 802.11ac/a/b/g/n, 433Mbps 5GHz + 300Mbps 2.4GHz

TP-Link Archer MR200. Wi-Fi band: Dual-band (2.4 GHz / 5 GHz), Top Wi-Fi standard: Wi-Fi 5 (802.11ac), WLAN data transfer rate (max): 433 Mbit/s. Ethernet LAN interface type: Fast Ethernet, Ethernet LAN data rates: 10,100 Mbit/s, Cabling technology: 10/100Base-T(X). Mobile network generation: 4G, 2G standards: Edge, GPRS, GSM, 3G standards: DC-HSPA+, HSPA, HSPA+, UMTS. Security algorithms: 64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK. Data link protocols: IPv4, IPv6





WAN connection		Protocols	
Ethernet WAN *	✓	DHCP client	1
DSL WAN *	×	DHCP server	✓
SIM card slot *	1	Universal Plug and Play (UPnP)	1
3G/4G USB modem compatibility *	×	Data link protocols	IPv4, IPv6
Wireless LAN features		Design	
Wi-Fi band * Top Wi-Fi standard * WLAN data transfer rate (max) *	Dual-band (2.4 GHz / 5 GHz) Wi-Fi 5 (802.11ac) 433 Mbit/s 802.11a, Wi-Fi 5 (802.11ac),	Product colour LED indicators On/off switch	Black
Wi-Fi standards	802.11a, Wi-Fi 5 (802.11ac), 802.11b, 802.11g, Wi-Fi 4 (802.11n)	Product type *	Tabletop router
WLAN data transfer rate (first band)	300 Mbit/s	Certificates	
WLAN data transfer rate (second	433 Mbit/s	Certification	CE, FCC, RoHS
band)		Packaging content	
Network		Cables included	LAN (RJ-45)
Ethernet LAN *	1	AC adapter included	1
Ethernet LAN interface type *	Fast Ethernet	Quick start guide	1
Ethernet LAN data rates Cabling technology	10,100 Mbit/s 10/100Base-T(X) IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n PPTP, L2TP, IPSec	Antenna	
Networking standards		Antenna design * Antennas quantity Detachable antenna(s) Transmit power	External 5 ✓ 0 dBmW
Mobile network		Power	
Mobile network generation	Image: state of the state o	Power source type *	AC
3G		Operational conditions	
4G 2G standards 3G standards 4G standard GSM bands supported UMTS bands supported 4G bands supported		Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	0 - 40 °C -40 - 70 °C 10 - 90% 5 - 90%

Ports & interfaces		System requirements			
Ethernet LAN (RJ-45) ports * USB port * Memory card slot(s) DC-in jack	4 ★ ★		Windows 2000, Windows 2000 Professional, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium x64, Windows 7 Home		
Management features			Premium x64, Windows 7 Professional, Windows 7		
Web-based management	•		Professional x64, Windows 7 Starter, Windows 7 Starter x64,		
Quality of Service (QoS) support	1		Windows 7 Ultimate, Windows 7		
Reset button	4		Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise		
Security			x64, Windows 8 Pro, Windows 8 Pro		
Security algorithms	64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK	Windows operating systems supported	x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1		
Firewall	✓		Pro, Windows 8.1 Pro x64, Windows		
Stateful Packet Inspection (SPI)	✓		8.1 x64, Windows Vista Business, Windows Vista Business x64.		
DoS attack prevention	1		Windows Vista Enterprise, Windows		
Filtering	1	Vista Enterprise x64, Windo Home Basic, Windows Vista	Home Basic, Windows Vista Home		
MAC address filtering	1		Basic x64, Windows Vista Home		
IP address filtering	•	Premium x64 Ultimate, Wir x64, Window XP Home x64 Professional,	Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64		

Linux operating systems supported Mac operating systems supported

Weight & dimensions			
Width	202 mm		
Depth	141 mm		
Height	33.6 mm		
Packaging data			
Micro to standard SIM card adapter	✓		
Nano to standard SIM card adapter	✓		
Logistics data			
Harmonized System (HS) code	85176990		
Other features			
Input current	1 A		

1

✓

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.