

## TP-Link Archer MR200 langaton reititin Nopea Ethernet Kaksitaajuus (2,4 GHz/5 GHz) 4G musta

Tuotemerkki : TP-Link Tuotekoodi: ARCHER MR200 V2

Tuotteen nimi: Archer MR200







WAN connection		Protocols	
Ethernet WAN *	1	DHCP client	✓
DSL WAN *	×	DHCP server	✓
SIM card slot *	✓	Universal Plug and Play (UPnP)	<b>✓</b>
3G/4G USB modem compatibility *	x	Data link protocols	IPv4, IPv6
Wireless LAN features		Design	
Wi-Fi band *	Dual-band (2.4 GHz / 5 GHz)	Product colour	Black
Top Wi-Fi standard *	Wi-Fi 5 (802.11ac)	LED indicators	✓
WLAN data transfer rate (max) *	433 Mbit/s	On/off switch	✓
Wi-Fi standards	802.11a, Wi-Fi 5 (802.11ac), 802.11b, 802.11g, Wi-Fi 4 (802.11n)	Product type *	Tabletop router
WLAN data transfer rate (first band)	•	Certificates	
WLAN data transfer rate (second	433 Mbit/s	Certification	CE, FCC, RoHS
band)	באומויו ככד	Packaging content	
Network		Cables included	LAN (RJ-45)
Ethernet LAN *	<b>✓</b>	AC adapter included	<b>✓</b>
Ethernet LAN interface type *	Fast Ethernet	Quick start guide	✓
Ethernet LAN data rates	10,100 Mbit/s	Antenna	
Cabling technology	10/100Base-T(X)	Antenna design *	External
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Antennas quantity	5
		Detachable antenna(s)	·
VPN support	PPTP, L2TP, IPSec	Transmit power	0 dBmW
Mobile network		Power	
Mobile network generation	4G	Power source type *	AC
3G	1	Operational conditions	
4G	✓	•	0.40.96
2G standards	Edge, GPRS, GSM	Operating temperature (T-T) Storage temperature (T-T)	0 - 40 °C -40 - 70 °C
3G standards	DC-HSPA+, HSPA, HSPA+, UMTS	Operating relative humidity (H-H)	10 - 90%
4G standard	LTE	Storage relative humidity (H-H)	5 - 90%
GSM bands supported	850,900,1800,1900 MHz	Storage relative numbers (11-11)	5 50/0
UMTS bands supported	900,2100 MHz		
4G bands supported	800,900,1800,2100,2600 MHz		

Ports & interfaces		System requirements	
Ethernet LAN (RJ-45) ports * USB port * Memory card slot(s) DC-in jack	4 × ×		Windows 2000, Windows 2000 Professional, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home
Management features			Premium x64, Windows 7 Professional, Windows 7
Web-based management Quality of Service (QoS) support Reset button	<i>y y</i>	Windows operating systems supported	Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 X1, Windows 8.1 Enterprise, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 Pro, Windows Vista Business, Windows Vista Business, Windows Vista Enterprise, Windows Vista Enterprise, Windows Vista Enterprise, Windows Vista Home Basic, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Security			
Security algorithms  Firewall  Stateful Packet Inspection (SPI)  DoS attack prevention	64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK		
Itering  AC address filtering	<b>✓</b>		
		Linux operating systems supported	✓
		Mac operating systems supported	✓
		Weight & dimensions	
		Width Depth Height	202 mm 141 mm 33.6 mm
		Packaging data	
		Micro to standard SIM card adapter	✓
		Nano to standard SIM card adapter	✓
		Logistics data	
		Harmonized System (HS) code	85176990
		Other features	
		Input current	1 A

