

## BenQ MH733 data projector Standard throw projector 4000 ANSI lumens DLP 1080p (1920x1080) White

Brand : BenQ Product code: 9H.JGT77.13E

**Product name:** MH733

- 4000 ANSI Lumens High Brightness
- Full HD 1080p Resolution
- USB Reader for PC-Less Presentations
- Networked Presentation
- AMX/Crestron/Extron Control System Compatibility

DLP, 4000 Lum, 1920 x 1080, 16:9, 30-300", 2x HDMI, 2x VGA, LAN, RS-232, USB, 296x120x221 mm

## BenQ MH733 data projector Standard throw projector 4000 ANSI lumens DLP 1080p (1920x1080) White:

BenQ MH733 delivers bright performance with versatility of USB and wireless presentations in diverse meeting situation for productive collaboration. MH733 guarantees efficient TCO and device maintenance with the LAN connectivity, support for leading display network control systems, and MH733's long lamp life.





Projector		Storage	
Screen size compatibility *	762 - 7620 mm (30 - 300") 4000 ANSI lumens	Card reader integrated *	×
Projector brightness *		Features	
Projection technology * DLP Projector native resolution * 1080p (1920x1080)		Noise level (economic mode)	29 dB
Contrast ratio (typical) * Native aspect ratio * Number of colours Horizontal scan range Vertical scan range Keystone correction, horizontal Keystone correction, vertical Matrix type	16000:1 16:9 1.073 billion colours 15 - 102 kHz 23 - 120 Hz 1000:200:100:100:100:100:100:100:100:100	On Screen Display (OSD)  On Screen Display (OSD) languages  Noise level *	Arabic, Bulgarian, Simplified Chinese, Traditional Chinese, Croatian, Czech, Danish, German, Dutch, English, Spanish, Finnish, French, Greek, Hindi, Hungarian, Indonesian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Romanian, Russian, Swedish, Thai, Turkish, Vietnamese 33 dB
Light source			33 UD
Light source type *	Lamp	Multimedia	
Service life of light source *	4000 h	Built-in speaker(s) *	<b>✓</b>
Service life of light source (economic mode)	8000 h	RMS rated power  Number of built-in speakers	10 W 1
Lamp power	240 W	Design	
Lens system	1 lamp(s)	Market positioning * Product type *	Business Standard throw projector
Focus * Focal length range	Manual 16.88 - 21.88 mm	Product colour * Placement	White
Aperture range (F-F)	2.59 - 2.87	Cable lock slot	Desktop, Ceiling
Zoom capability		cable lock slot	
' '	✓	Cable lock slot type	Kensington
Zoom type	Manual	Cable lock slot type <b>Display</b>	
, ,		7.	
Zoom type Zoom ratio	Manual 1.3:1	Display	Kensington
Zoom type Zoom ratio Throw ratio	Manual 1.3:1 1.15 - 1.5	Display Built-in display *	Kensington
Zoom type Zoom ratio Throw ratio Offset	Manual 1.3:1 1.15 - 1.5	Display Built-in display * Power	Kensington  X
Zoom type Zoom ratio Throw ratio Offset Video	Manual 1.3:1 1.15 - 1.5 105%	Display Built-in display * Power Power source *	X  AC 320 W 0.5 W
Zoom type Zoom ratio Throw ratio Offset  Video Analog signal format system *	Manual 1.3:1 1.15 - 1.5 105% NTSC, PAL, SECAM	Display  Built-in display *  Power  Power source *  Power consumption (typical) *  Power consumption (standby) *  Power consumption (max)	X  AC 320 W
Zoom type Zoom ratio Throw ratio Offset  Video Analog signal format system * Full HD *	Manual 1.3:1 1.15 - 1.5 105%  NTSC, PAL, SECAM  ✓	Display  Built-in display *  Power  Power source *  Power consumption (typical) *  Power consumption (standby) *	X  AC 320 W 0.5 W

Video		Power	
Supported video modes	480i, 480p, 576i, 576p, 720p, 1080i, 1080p	AC input voltage AC input frequency	100 - 240 V 50 - 60 Hz
Ports & interfaces		Operational conditions	
HDMI connector type USB 2.0 ports quantity Serial interface type * PC Audio in	Full-size 2 RS-232 ✓	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	0 - 40 °C -20 - 60 °C 10 - 90% 10 - 90%
PC Audio out	✓	Weight & dimensions	
VGA (D-Sub) ports quantity * HDMI ports quantity * DVI port * Mobile High-Definition Link (MHL)	2 2 <b>X</b>	Width Depth Height Weight *	296 mm 221 mm 120 mm 2.5 kg
AC (power) in	<b>✓</b>	Packaging content	
Network		Remote control included *	✓
Ethernet LAN * Ethernet LAN (RJ-45) ports Wi-Fi *	1 X	Batteries included Cables included Quick start guide Manual Warranty card	AC, VGA
		Logistics data	
		Harmonized System (HS) code	85286200
		Other features	
		RS-232 ports Security updates end date	1 31/12/2024





840046037307

0840046037307



4718755069734

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.