

Epson TM-U220PB (057): Parallel, PS, EDG

Tuotemerkki : Epson

Tuotekoodi: C31C517057

Tuotteen nimi : Epson TM-U220PB (057): Parallel, PS, EDG

Epson TM-U220PB

Epson TM-U220PB (057): Parallel, PS, EDG. Tulostustekniikka: Pistematriisi, Malli: Maksupäätetulostin, Tulostusnopeus: 4 lps. Suurin rullan halkaisija: 8,3 cm, Tuetut paperin leveydet: 76, 69.5, 57.5 mm. Yhteysteknologia: Langallinen, Vakioliitännät: Rinnakkainen. Äänenpainetaso (tulostus): 64 dB, Keskimääräinen vikaantumisaika: 180000 h, Automaattisen leikkaajan kestävyys: 0,8 miljoonaa leikkausta. Tuotteen väri: Harmaa

Printing		System requirements	
Print speed	4 lps	Compatible operating systems	Windows 2000, XP, Vista
Character size	1.6 x 3.1 mm	Weight & dimensions	
Character density	16 cpi	Width	160 mm
Print technology *	Dot matrix	Depth	248 mm
Type *	POS printer	Height	139 mm
Paper handling		Weight	2.5 kg
Maximum roll diameter	8.3 cm	Packaging data	
Supported paper width	76, 69.5, 57.5 mm	Quantity per pack	1 pc(s)
Ports & interfaces		Package width	240 mm
Parallel connector	✓	Package depth	375 mm
Connectivity technology *	Wired	Package height	250 mm
Standard interfaces	Parallel	Package weight	5.2 kg
Network		Packaging content	
Ethernet LAN *	✗	Quick start guide	✓
Wi-Fi *	✗	AC adapter included	✓
Features		Print technology	
Sound pressure level (printing)	64 dB	Column capacity	40
Mean time between failures (MTBF)	180000 h	Logistics data	
Autocutter durability	0.8 million cuts	Harmonized System (HS) code	84433210
Standard media sizes	63 / 57 /47 mm	Products per pallet	56 pc(s)
Country of origin	China	Products per pallet layer	8 pc(s)
Safety	UL, CSA, TÜV (EN60950)	Pallet gross width	120 cm
Design		Pallet gross height	100 cm
Product colour *	Grey	Products per pallet (UK)	84 pc(s)
Power		Products per pallet layer (UK)	12 pc(s)
AC input voltage	24 V	Pallet length (UK)	2.25 m
Operational conditions		Other features	
Storage temperature (T-T)	-10 - 50 °C	Dimensions (WxDxH)	160 x 248 x 138.5 mm
Operating relative humidity (H-H)	10 - 90%	Electromagnetic compatibility	VCCI class A, FCC class A, CE marking, AS / NZS 3548 class B
Storage relative humidity (H-H)	10 - 90%	Mean cycles between failures (MCBF)	18000000



8715946191126

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-FEB-2025. Prints or copies of Information are only valid on the printed Publication date