



ATEN VE807-AT-G AV-signaalin jatkaja AV-lähetin ja -vastaanotin Valkoinen

Tuotemerkki : ATEN

Tuotekoodi: VE807-AT-G

Tuotteen nimi : VE807-AT-G



ATEN VE807-AT-G. Malli: AV-lähetin ja -vastaanotin, Enimmäiserottelutarkkuus: 1920 x 1200 pikseliä, Tuetut kaapelityypit: Cat5e, Cat6. Yhteysteknologia: Langallinen. Käyttöjännite (lähetin): 9 V, Käyttöjännite (vastaanotin): 9 V, Tehonkulutus (lähetin) (max): 1,35 W. Paino: 500 g, Vastaanottimen mitat (L x S x K): 44,4 x 68,6 x 40 mm, Vastaanottimen paino: 180 g. Lukumäärä per pakkaus: 2 kpl, Pakkauksen leveys: 59 mm, Pakkauksen syvyys: 239 mm



Features		Power	
Type *	AV transmitter & receiver	Power consumption (receiver) (max)	0.81 W
Maximum resolution *	1920 x 1200 pixels	External power adapter	✓
Cable types supported	Cat5e, Cat6	Operational conditions	
Maximum transfer distance	60 m	Operating temperature (T-T)	0 - 50 °C
Audio system	stereo	Storage temperature (T-T)	-20 - 60 °C
Electrostatic Discharge (ESD) protection	15 kV	Operating relative humidity (H-H)	0 - 80%
LED indicators	✓	Weight & dimensions	
Supported video modes	1080i, 1080p	Weight	500 g
Bandwidth	6.75 Gbit/s	Receiver dimensions (WxDxH)	44.4 x 68.6 x 40 mm
Bandwidth	225 MHz	Receiver weight	180 g
HDCP	✓	Transmitter dimensions (WxDxH)	44.4 x 68.6 x 40 mm
Material	Metal	Transmitter weight	180 g
3D	✓	Packaging data	
Plug and Play	✓	Quantity per pack	2 pc(s)
Impedance	100 Ω	Package width	59 mm
Product colour	White	Package depth	239 mm
Ports & interfaces		Package height	160 mm
Connectivity technology *	Wired	Package weight	610 g
RJ-45 input ports	2	Packaging content	
RJ-45 output ports	2	AC adapter included	✓
HDMI in	1	Manual	✓
Number of HDMI outputs	1	Technical details	
Video in	1	Compliance certificates	RoHS
Video out	1	Logistics data	
Audio input	1	Master (outer) case width	250 mm
Audio output	1	Master (outer) case length	325 mm
DC-in jack	✓	Master (outer) case height	175 mm
Power		Master (outer) case gross weight	3.41 kg
Operating voltage (transmitter)	9 V	Master (outer) case net weight	2.5 kg
Operating voltage (receiver)	9 V	Products per master (outer) case	5 pc(s)
Power consumption (transmitter) (max)	1.35 W		



4719264645716

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 27-DEC-2024. Prints or copies of Information are only valid on the printed Publication date