

Seagate Barracuda Pro sisäinen kiintolevy 1 TB 7200 RPM 128 MB 2.5" Serial ATA III

Tuotemerkki : Seagate Tuoteperhe: Barracuda Tuotekoodi: ST1000LM049

Tuotteen nimi: Pro

Seagate Barracuda Pro. HDD-kapasiteetti: 1 TB, HDD-nopeus: 7200 RPM, Tallennusaseman

puskurointikoko: 128 MB, HDD-koko: 2.5", Käyttöliittymä: Serial ATA III





HDD capacity * 1 TB Operating relative humidity (H-H) 5 - 90% HDD speed * 7200 RPM Storage relative humidity (H-H) 5 - 95% Storage drive buffer size * 128 MB Operating vibration 2 G HDD size * 2.5" Non-operating vibration 5 G Interface * Serial ATA III Operating altitude -304.8 - 304.8 m Type * HDD Non-operating altitude -304.8 - 12192 m Component for * PC Operating shock 400 G HDD interface transfer rate 6 Gbit/s Non-operating shock 1000 G HDD sustained transfer rate 160 MiB/s Weight & dimensions HDD number of heads 2 Width 69.8 mm Track to track seek time 0.5 ms Height 7 mm Average latency 11.5 ms Depth 100.3 mm Bytes per sector 4096 Weight 90 g Start/stop cycles 600000 Weight 90 g Workload rate limit 55 TB/year Packaging data Power Operating voltage 5 V Logistics data Harmonized System (HS) code 84717050	Features		Operational conditions	
HDD number of heads 7 Track to track seek time Average latency 11.5 ms Bytes per sector Start/stop cycles Workload rate limit Power Operating voltage 5 V Start-up current 2 Width 69.8 mm 7 mm 100.3 mm Weight 90 g Weight 90 g 4096 Weight Packaging data Quantity per pack Logistics data Harmonized System (HS) code 84717050	HDD speed * Storage drive buffer size * HDD size * Interface * Type * Component for * HDD interface transfer rate	7200 RPM 128 MB 2.5" Serial ATA III HDD PC 6 Gbit/s e 160 MiB/s 2 0.5 ms 11.5 ms 4096 600000	Storage relative humidity (H-H) Operating vibration Non-operating vibration Operating altitude Non-operating altitude Operating shock Non-operating shock	5 - 95% 2 G 5 G -304.8 - 3048 m -304.8 - 12192 m 400 G
Power Quantity per pack 1 pc(s) Operating voltage 5 V Logistics data Start-up current 1 A Harmonized System (HS) code 84717050	Track to track seek time Average latency Bytes per sector Start/stop cycles		Width Height Depth Weight	7 mm 100.3 mm
	Power Operating voltage	5 V	Quantity per pack Logistics data	
Operational conditions Operating temperature (T-T) 0 - 60 °C Drive ready time 3.2 s	Operational conditions		Other features	















Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.