



## D-Link DGS-1210-28 verkkokytin Hallittu L2 Gigabit Ethernet (10/100/1000) 1U musta

**Tuotemerkki :** D-Link

**Tuotekoodi:** DGS-1210-28

**Tuotteen nimi :** DGS-1210-28



D-Link DGS-1210-28. Kytin tyyppi: Hallittu, Kytinkerros: L2. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 24. Täysin kaksipuolinen. MAC-osoitetaulukko: 8000 entries, Kytkentäkapasiteetti: 56 Gbit/s. Verkkostandardit: IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x. Virtaliitin: AC-in-liitin. Telineasennus, Kotelo: 1U



| Management features                             |  | Security                          |                          |
|---|--|-----------------------------------|--------------------------|
| Switch type *                                   | Managed  | DHCP features                     | DHCP server, DHCP client |
| Switch layer                                    | L2   | Access Control List (ACL)         | ✓                        |
| Quality of Service (QoS) support                | ✓  | IGMP snooping                     | ✓                        |
| Web-based management                            | ✓  | MAC address filtering             | ✓                        |
| ARP inspection                                  | ✓  | Loop protection                   | ✓                        |
| Configuring Location Settings (CLI)             | ✓  | <b>Multicast features</b>         |                          |
| System event log                                | ✓  | Multicast support                 | ✓                        |
| MIB support                                     | ✓  | <b>Design</b>                     |                          |
| <b>Ports &amp; interfaces</b>                   |  | Rack mounting *                   | ✓                        |
| Basic switching RJ-45 Ethernet ports quantity * | 24   | Stackable *                       | ✓                        |
| Basic switching RJ-45 Ethernet ports type *     | Gigabit Ethernet (10/100/1000)                     | Form factor                       | 1U                       |
| Combo SFP ports quantity                        | 4  | Product colour                    | Black                    |
| Power connector                                 | AC-in jack   | LED indicators                    | ✓                        |
| <b>Network</b>                                  |  | <b>Performance</b>                |                          |
| Networking standards *                          | IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x | Memory type                       | DDR3-SDRAM               |
| Copper ethernet cabling technology              | 10BASE-T, 100BASE-TX, 1000BASE-T                   | Internal memory                   | 256 MB                   |
| Port mirroring                                  | ✓  | Flash memory                      | 32 MB                    |
| Full duplex                                     | ✓  | Noise level                       | 55.2 dB                  |
| Flow control support                            | ✓  | Mean time between failures (MTBF) | 992594 h                 |
| Link aggregation                                | ✓  | <b>Power</b>                      |                          |
| Broadcast storm control                         | ✓  | Power source *                    | AC                       |
| Auto MDI/MDI-X                                  | ✓  | Power supply included *           | ✓                        |
| Spanning tree protocol                          | ✓  | AC input voltage                  | 100 - 240 V              |
| Head-of-line (HOL) blocking                     | ✓  | AC input frequency                | 50/60 Hz                 |
| Auto-negotiation                                | ✓  | Power consumption (max)           | 17.32 W                  |
| VLAN support                                    | ✓  | <b>Power over Ethernet (PoE)</b>  |                          |
|   |  | Power over Ethernet (PoE) *       | ✗                        |

| Network              |              | Operational conditions            |             |
|----------------------|--------------|-----------------------------------|-------------|
| Number of VLANs      | 256          | Operating temperature (T-T)       | -5 - 50 °C  |
| Data transmission    |              | Storage temperature (T-T)         | -40 - 70 °C |
| Switching capacity * | 56 Gbit/s    | Operating relative humidity (H-H) | 0 - 95%     |
| Forwarding rate      | 77.4 Mpps    | Storage relative humidity (H-H)   | 0 - 95%     |
| MAC address table *  | 8000 entries | Heat dissipation                  | 59.09 BTU/h |
| Store-and-forward    | ✓            | Weight & dimensions               |             |
| Jumbo frames support | ✓            | Width                             | 440 mm      |
| Jumbo frames         | 10000        | Depth                             | 140 mm      |
| Packet buffer memory | 4.1 MB       | Height                            | 44 mm       |
|                      |              | Weight                            | 2.15 kg     |



0790069373008



790069373008




0790069372971



790069372971



0790069372964



790069372964

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.