

D-Link DEM-211 lähetin-vastaanotinmoduuli Valokuitu 100 Mbit/s SFP 1310 nm

Tuotemerkki : D-Link

Tuotekoodi: DEM-211

Tuotteen nimi : DEM-211



D-Link DEM-211. SFP-vastaanottimen tyyppi: Valokuitu, Tiedonsiirron enimmäisnopeus: 100 Mbit/s, PCI-väylä: SFP. Tuotteen väri: Metallinen, Kotelo: Pistokeytkentä, Yhteensopivat tuotteet: DES-1228, DES-1228P, DES-3252P, DES-3228PA, DES-1252, DGS-3612G. Maksimijännite: 3,3 V. Turvallisuus: FDA/CDRH, TUV, UL, Sertifiointi: RoHS. Tuotteen leveys: 57,9 mm, Tuotteen syvyys: 12,7 mm, Tuotteen korkeus: 7,62 mm

Performance		Operational conditions	
SFP transceiver type *	Fiber optic	Storage relative humidity (H-H)	5 - 90%
Maximum data transfer rate *	100 Mbit/s	Weight & dimensions	
Interface type *	SFP	Width	57.9 mm
Multi-mode fiber (MMF) supported	✓	Depth	12.7 mm
Fiber optic connector	LC	Height	7.62 mm
Fiber cable diameters supported (core/cladding)	50/125,62.5/125 µm	Weight	13.6 g
Maximum transfer distance	2000 m	Packaging data	
Wavelength	1310 nm	Package width	74 mm
Link budget	13 dB	Package depth	131 mm
Networking standards	IEEE 802.3u	Package height	49 mm
Cabling technology	100Base-FX	Package weight	64 g
Fiber ethernet cabling technology	100BASE	Logistics data	
Duplex system	Full, Half	Shipping (inner) case length	36 cm
Features		Shipping (inner) case width	26 cm
Product colour	Metallic	Shipping (inner) case height	31 cm
Form factor	Plug-in	Shipping (inner) case net weight	3.2 kg
Hot-swap	✓	Products per shipping (inner) case	50 pc(s)
Compatible products	DES-1228, DES-1228P, DES-3252P, DES-3228PA, DES-1252, DGS-3612G	Pallet gross weight (air)	246.8 kg
Power		Master (outer) cases per pallet (air)	54 pc(s)
Maximum voltage	3.3 V	Products per pallet (air)	2700 pc(s)
Certificates		Pallet gross length	102 cm
Safety	FDA/CDRH, TUV, UL	Pallet gross width	122 cm
Certification	RoHS	Pallet height (air)	199 cm
Operational conditions		Pallet gross weight (sea)	246.8 kg
Operating temperature (T-T)	0 - 70 °C	Master (outer) cases per pallet (sea)	54 pc(s)
Storage temperature (T-T)	-40 - 85 °C	Products per pallet (sea)	2700 pc(s)
Operating relative humidity (H-H)	10 - 90%	Pallet height (sea)	199 cm
		Shipping (inner) case gross weight	4.2 kg
		Harmonized System (HS) code	85369010



7900692981270



0790069298127



790069298127

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.