



## APC AP6020A power distribution unit (PDU) 13 AC outlet(s) 0U/1U Black



**Brand :** APC

**Product code:** AP6020A

**Product name :** AP6020A

NetShelter Basic Rack PDU, 0U, 1PH, 3.3kW, 100-240V 20A or 200-240V 16A, 13 C13 outlets, C20 inlet

[APC AP6020A power distribution unit \(PDU\) 13 AC outlet\(s\) 0U/1U Black:](#)

Reliable rack power distribution designed to increase manageability and efficiency in the data center The output and input connections are (13) C13 Real-time remote monitoring of connected loads User-defined alarms warn IT and data center managers of potential circuit overloads to prevent accidental power loss to critical equipment.

APC AP6020A. PDU types: Basic, Rack capacity: 0U/1U, Type: Single-phase. AC outlets quantity: 13 AC outlet(s), AC outlet types: C13 coupler, Power plug: C20 coupler. Certification: cUL Listed, CE, EAC, IRAM, PSE, UL Listed, VDE, REACH. Nominal input voltage: 100-240 V, Maximum current: 20 A, AC input frequency: 50 - 60 Hz. Dimensions (WxDxH): 44 x 93 x 388 mm, Weight: 1.5 kg

Design		Power	
PDU types *	Basic	Maximum input current per phase	16 A
Type	Single-phase	Maximum total current draw per phase	16 A
Rack capacity *	0U/1U	Maximum power	3680 W
Mounting	Horizontal/Vertical	Weight & dimensions	
Product colour	Black	Dimensions (WxDxH)	44 x 93 x 388 mm
Ports & interfaces		Weight	1.5 kg
AC outlets quantity *	13 AC outlet(s)	Packaging data	
Power plug	C20 coupler	Package dimensions (WxDxH)	210 x 76 x 436 mm
AC outlet types *	C13 coupler	Package weight	2.02 kg
Output connections	IEC 320 C13	Operational conditions	
Features		Operating temperature (T-T)	0 - 50 °C
Certification	cUL Listed, CE, EAC, IRAM, PSE, UL Listed, VDE, REACH	Storage temperature (T-T)	-15 - 60 °C
Power		Operating relative humidity (H-H)	5 - 95%
Nominal input voltage *	100-240 V	Storage relative humidity (H-H)	5 - 95%
AC input frequency	50 - 60 Hz	Operating altitude	0 - 3048 m
Maximum current *	20 A	Technical details	
Load capacity	3680 VA	Compliance certificates	RoHS



0731304327806



731304327806

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.