# ATEN

## ATEN KN2140VA-AX-G KVM-kytkin Telineasennus musta, Harmaa

**Tuotemerkki :** ATEN

**Tuotteen nimi :** KN2140VA-AX-G

**Tuotekoodi:** KN2140VA-AX-G

ATEN KN2140VA-AX-G. Näppäimistöportin liitin: USB, Hiiriportin liitin: USB, Videoportin tyyppi: DVI-I. Kaapelitekniikka: 10/100/1000Base-T(X), Verkkostandardit: IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, Tietoturva-algoritmit: 3DES, 56-bit AES, 128-bit RC4, 256-bit AES, FIPS 140-2, SSL/TLS. HD-tyyppi: WUXGA, Enimmäiserottelutarkkuus: 1920 x 1200 pikseliä, Videokaistanleveys: 60 Hz. Tuotteen väri: musta, Harmaa, Telineen kapasiteetti: 1U, Kotelon materiaali: Metalli. Voimanlähde: AC, Tulojännite: 100 - 240 V, AC-syöttötaajuus: 50 / 60 Hz

### Ports & interfaces

| | |
|---|---|
| Number of computers controlled * | 40 |
| Keyboard port type * | USB |
| Mouse port type * | USB |
| Video port type * | DVI-I |
| DVI-I ports quantity | 1 |
| Console ports * | DVI-I, USB A |
| Console USB ports quantity | 2 |
| USB hub | ✔ |
| USB 2.0 Type-A hub ports quantity | 3 |
| USB connector type | Mini-USB B, USB Type-A |
| Audio connections | ✔ |
| DC-in jack | ✘ |

### Network

| | |
|---|---|
| Ethernet LAN | ✔ |
| Ethernet LAN (RJ-45) ports | 42 |
| Cabling technology | 10/100/1000Base-T(X) |
| Networking standards | IEEE 802.3, IEEE 802.3ab, IEEE 802.3u |
| Security algorithms | 3DES, 56-bit AES, 128-bit RC4, 256-bit AES, FIPS 140-2, SSL/TLS |

### Performance

| | |
|---|---|
| HD type * | WUXGA |
| Maximum resolution * | 1920 x 1200 pixels |
| Video bandwidth | 60 Hz |
| Data transfer rate (max) | 1000 Gbit/s |
| Scan interval | 1,255 s |
| Number of users | 64 user(s) |
| Firmware upgradeable | ✔ |

### Design

| | |
|---|---|
| Rack mounting * | ✔ |
| Rack capacity | 1U |
| Product colour * | Black, Grey |
| Housing material | Metal |

### Power

| | |
|---|---|
| Input voltage | 100 - 240 V |
| AC input frequency | 50 / 60 Hz |
| Input current | 1 A |
| External power adapter | ✘ |

### System requirements

| | |
|---|---|
| Windows operating systems supported | ✔ |
| Linux operating systems supported | ✔ |
| Mac operating systems supported | ✔ |

### Sustainability

| | |
|---|---|
| Compliance certificates | RoHS |

### Operational conditions

| | |
|---|---|
| Operating temperature (T-T) | 0 - 40 °C |
| Storage temperature (T-T) | -20 - 60 °C |
| Operating relative humidity (H-H) | 0 - 80% |

### Weight & dimensions

| | |
|---|---|
| Width | 433.6 mm |
| Depth | 412.1 mm |
| Height | 44 mm |
| Weight | 6.23 kg |

### Packaging data

| | |
|---|---|
| Package width | 506 mm |
| Package depth | 575 mm |
| Package height | 130 mm |
| Package weight | 7.49 kg |

### Packaging content

| | |
|---|---|
| Cables included | AC |
| Manual | ✔ |
| Rack mount kit | ✔ |

### Logistics data

| | |
|---|---|
| Master (outer) case net weight | 6.23 kg |

## Design

| | |
|---|---|
| Wired remote switch | ✔ |
| Cascadable | ✔ |
| LED indicators | ✔ |
| Push button | ✔ |
| Hot keys | ✔ |

## Display

| | |
|---|---|
| Built-in display * | ✘ |

## Power

| | |
|---|---|
| Power source | AC |

## Logistics data

| | |
|---|---|
| Harmonized System (HS) code | 85176200 |
| Master (outer) case width | 506 mm |
| Master (outer) case length | 575 mm |
| Master (outer) case height | 130 mm |
| Master (outer) case gross weight | 7.61 kg |
| Products per master (outer) case | 1 pc(s) |

4710423775688

4719264644139