



ATEN VE816R-AT-G AV-signaalin jatkaja AV-vastaanotin musta

Tuotemerkki : ATEN

Tuotekoodi: VE816R-AT-G

Tuotteen nimi : VE816R-AT-G

ATEN VE816R-AT-G. Malli: AV-vastaanotin, Enimmäiserottelutarkkuus: 4096 x 2160 pikseliä, Tuetut kaapelityypit: Cat5e, Cat6, Cat6a. Yhteysteknologia: Langallinen. Tuotteen leveys: 166 mm, Tuotteen syvyys: 124,9 mm, Tuotteen korkeus: 29 mm. Lukumäärä per pakkaus: 1 kpl, Pakkauksen leveys: 62 mm, Pakkauksen syvyys: 283 mm. Tukkupakkauksen leveys: 300 mm, Tuotepakkauksen pituus: 336 mm, Tukkupakkauksen korkeus: 194 mm



| Features | | Operational conditions | |
|--------------------------------|--------------------------|-----------------------------------|-------------|
| Type * | AV receiver | Operating relative humidity (H-H) | 0 - 80% |
| Maximum resolution * | 4096 x 2160 pixels | Storage relative humidity (H-H) | 0 - 80% |
| Cable types supported | Cat5e, Cat6, Cat6a | Weight & dimensions | |
| Maximum transfer distance | 100 m | Width | 166 mm |
| Maximum refresh rate | 60 Hz | Depth | 124.9 mm |
| Supported graphics resolutions | 3840 x 2160, 4096 x 2160 | Height | 29 mm |
| Bandwidth | 10.2 Gbit/s | Weight | 870 g |
| Bandwidth | 340 MHz | Packaging data | |
| HDCP | ✓ | Quantity per pack | 1 pc(s) |
| Material | Metal | Package width | 62 mm |
| 3D | ✓ | Package depth | 283 mm |
| Rack mounting | ✓ | Package height | 173 mm |
| Firmware upgradeable | ✓ | Package weight | 1 kg |
| Plug and Play | ✓ | Packaging content | |
| Impedance | 100 Ω | AC adapter included | ✓ |
| HDCP version | 2.2 | Manual | ✓ |
| Product colour | Black | Logistics data | |
| HDBaseT certified | ✓ | Master (outer) case width | 300 mm |
| Ports & interfaces | | Master (outer) case length | 336 mm |
| Connectivity technology * | Wired | Master (outer) case height | 194 mm |
| RJ-45 input ports | 1 | Master (outer) case gross weight | 5.2 kg |
| HDBaseT port | ✓ | Master (outer) case net weight | 4.35 kg |
| Number of HDMI outputs | 1 | Products per master (outer) case | 5 pc(s) |
| DC-in jack | ✓ | Operational conditions | |
| Operating temperature (T-T) | 0 - 40 °C | Operating temperature (T-T) | 0 - 40 °C |
| Storage temperature (T-T) | -20 - 60 °C | Storage temperature (T-T) | -20 - 60 °C |



4719264645921

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 01-MAR-2025. Prints or copies of Information are only valid on the printed Publication date