

## TP-Link EAP225-Outdoor V3 867 Mbit/s Valkoinen Power over Ethernet -tuki

Tuotemerkki : TP-Link

Tuotekoodi: EAP225-OUTDOOR V1

Tuotteen nimi : EAP225-Outdoor V3

TP-Link EAP225-Outdoor V3. 2,4 GHz, 5 GHz, Tiedonsiirron enimmäisnopeus: 867 Mbit/s. Tietoturvaalgoritmit: WPA-Enterprise, WPA-PSK, WPA2-Enterprise, WPA2-PSK. Ethernet LAN -datanopeudet: 10,100,1000 Mbit/s. Power over Ethernet -tuki. Tuotteen väri: Valkoinen

Features		Design	
2.4 GHz *	1	Placement *	Ceiling, Wall
5 GHz *	1	Product colour *	White
6 GHz *	×	Reset button	1
Maximum data transfer rate *	867 Mbit/s	Antenna	
Maximum data transfer rate (2.4 GHz)	300 Mbit/s	Antenna type * Antenna direction type	External Omni-directional
Maximum data transfer rate (5 GHz)	867 Mbit/s	Antenna features	Detachable antenna
Ethernet LAN data rates	10,100,1000 Mbit/s	Antennas quantity	2
Frequency band	2.4 - 5 GHz	Antenna gain level (max)	4 dBi
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3u	Certificates	
		Certification	CE[]FCC[]RoHS
МІМО	✓	Weight & dimensions	
MIMO type	Multi User MIMO	Width	214.9 mm
Wi-Fi Multimedia (WMM)/(WME)	1	Depth	46 mm
Rate limiting	1	Height	26.7 mm
Band steering	1	Packaging data	
Airtime Fairness (ATF)	1	Package width	270 mm
Quality of Service (QoS) support	1	Package depth	140 mm
Security		Package height	100 mm
Security algorithms *	WPA-Enterprise, WPA-PSK, WPA2-	Package weight	640 g
	Enterprise, WPA2-PSK	Packaging content	
Number of SSID supported	16	Quantity per pack	1 pc(s)
Remote Authentication Dial-In User Service (RADIUS)	1	AC adapter included	✓
Management features		PoE adapter included	✓
-		Mounting kit	✓
Web-based management	✓	Quick start guide	1

Management features		Operational conditions	
Syslog	1	Operating relative humidity (H-H)	10 - 90%
Ports & interfaces		Operating temperature (T-T) Storage temperature (T-T)	-30 - 70 °C -40 - 70 °C
Ethernet LAN (RJ-45) ports *	1	Storage relative humidity (H-H)	5 - 90%
Power		Logistics data	
Power over Ethernet (PoE) *	<ul> <li>Image: A set of the set of the</li></ul>	Harmonized System (HS) code	85176990
Power over Ethernet (PoE) type supported	Active PoE, Passive PoE		
Output voltage	24 V		
Power consumption (typical)	10.5 W		



6935364083588

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.