

APC MGE Galaxy 3500 20kVA 400V UPS-virtalähde 16000 W

Tuotemerkki : APC Tuotekoodi: G35T20KH3B4S

Tuotteen nimi: MGE Galaxy 3500 20kVA 400V

APC MGE Galaxy 3500 20kVA 400V. Kokonaislähtöteho (VA): 20 kVA, Lähtöteho: 16000 W, Syötteen taajuus: 40/70 Hz. Akkuteknologia: Sealed Lead Acid (VRLA), Akun latausaika: 5 h. Tuotteen väri: musta. Sertifiointi: CE,EN 50091-2,EN/IEC 62040-3,EN/IEC 62040-1-1,IEC 61000-3-2,IEC 61000-3-3,ISO 14001,ISO.... Paino: 535 kg



Features		Operational conditions	
Output power * 1 Input frequency * 4 Maximum current 2 Emergency Power Off (EPO) Noise level 5	20 kVA 16000 W 40/70 Hz 27 A ✓ 51.3 dB	Operating altitude Non-operating altitude	0 - 999.9 m 0 - 15000 m
		Certificates	
		Certification	CE,EN 50091-2,EN/IEC 62040-3,EN/IEC 62040-1-1,IEC 61000-3-2,IEC 61000-3-3,ISO 14001,ISO 9001,VFI-SS-111
Battery		Weight & dimensions	
Battery technology Battery recharge time	Sealed Lead Acid (VRLA) 5 h	Weight	535 kg
Replacement battery cartridge	2	Packaging data	
Design		Package weight	565 kg
Product colour *	Black	Logistics data	
Operational conditions		Harmonized System (HS) code	85078000
Operating temperature (T-T)	0 - 40 °C	Other features	
Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	-15 - 45 °C 0 - 95% 0 - 95%	Battery type	VRLA
		Output connections	1×4 -wire (3PH + G) 1×5 -wire (3PH + N + G) 1×5 -wire Terminals
		Input connection type	5-wire (3PH $+$ N $+$ G)
		Dimensions (WxDxH)	523 x 838 x 1491 mm
		Nominal output voltage	400 V
		Output voltage note	+/-1%, +/- 5%
		Package dimensions (WxDxH)	650 x 1062 x 1643 mm

