

## APC MGE Galaxy 3500 20kVA 400V 3:1 UPS-virtalähde 16000 W

Tuotemerkki : APC Tuotekoodi: G35T20K3I2B4S

Tuotteen nimi: MGE Galaxy 3500 20kVA 400V 3:1

APC MGE Galaxy 3500 20kVA 400V 3:1. Kokonaislähtöteho (VA): 20 kVA, Lähtöteho: 16000 W, Syötteen taajuus: 40/70 Hz. Akkuteknologia: Sealed Lead Acid (VRLA), Akun latausaika: 5 h. Tuotteen väri: musta. Sertifiointi: CE,EN 50091-2,EN/IEC 62040-3,EN/IEC 62040-1-1,IEC 61000-3-2,IEC 61000-3-3,ISO 14001,ISO.... Paino: 472 kg



Features		Operational conditions	
Output power * Output power * Input frequency * Maximum current	20 kVA 16000 W 40/70 Hz 27 A	Storage relative humidity (H-H) Operating altitude Non-operating altitude	0 - 95% 0 - 999.9 m 0 - 15000 m
		Certificates	
Emergency Power Off (EPO) Noise level Battery	<b>√</b> 51.3 dB	Certification	CE,EN 50091-2,EN/IEC 62040-3,EN/IEC 62040-1-1,IEC 61000-3-2,IEC 61000-3-3,ISO
Battery technology	Sealed Lead Acid (VRLA)		14001,ISO 9001,VFI-SS-111
Battery recharge time	5 h	Weight & dimensions	
Replacement battery cartridge	2	Weight	472 kg
Design		Packaging data	
Product colour *	Black	Package weight	505 kg
Operational conditions		Other features	
Operating temperature (T-T)	0 - 40 °C	Battery type	VRLA
Storage temperature (T-T) Operating relative humidity (H-H)	-15 - 45 °C 0 - 95%	Output connections	$1 \times 4$ -wire (3PH + G) $1 \times 5$ -wire (3PH + N + G) $1 \times 5$ -crew Terminals
		Input connection type	5-wire (3PH + N + G)
		Dimensions (WxDxH)	523 x 838 x 1491 mm
		Output voltage note	+/-1%, +/- 5%
		Package dimensions (WxDxH)	650 x 1062 x 1643 mm

