

Epson FX-2190II dot matrix printer 240 x 144 DPI 738 cps

Brand : Epson

Product code: C11CF38401

Product name : FX-2190II



- Market-leading print speeds: Complete your high-volume print runs even faster
 - Very low TCO: Cheap, long-lasting consumables and low power use
 - Even better reliability: Improved by 25 percent to 25,000 power-on hours
 - Smaller footprint: Allows for easy placement within a business environment
 - Energy Star compliant: To ensure the best possible energy efficiency
- Impact Dot Matrix, 9pins, 136columns, 18 Needles (2 x 9), 738chars/s, 240 x 144DPI, USB, Ethernet, 54W, 55dB, 128kB, ESC/P, IBM PPDS
- Epson FX-2190II. Maximum print speed: 738 cps, Maximum resolution: 240 x 144 DPI, Maximum print speed (draft): 463 cps. Maximum print size: A3 (297 x 420 mm), Paper tray media types: Envelopes, Continuous paper thickness range: 0.46 - 0.46 mm. Product colour: Black, Buffer size: 128 KB, Sound pressure level (printing): 55 dB. Standard interfaces: Parallel, USB. Print head: 9-pin, Print direction: Bidirectional, Print head life: 400 million characters

Printing		Power	
Maximum resolution *	240 x 144 DPI	Power consumption (economy mode)	0.5 W
Maximum printing width (columns) *	136	Operational conditions	
Colour *	×	Operating temperature (T-T)	5 - 35 °C
Maximum print speed *	738 cps	Storage temperature (T-T)	-30 - 60 °C
Maximum print speed (draft)	463 cps	Operating relative humidity (H-H)	10 - 80%
Maximum print speed (NLQ)	115 cps	Storage relative humidity (H-H)	30 - 60%
Character pitch	10,12,15 cpi	Weight & dimensions	
Maximum number of copies	6 copies	Width	612 mm
Built-in barcodes	CODABAR (NW-7), Code 128 (A/B/C), Code 39, Industrial 2/5, Matrix 2/5, POSTNET, UPC-A, UPC-E	Depth	375 mm
Bitmap fonts	Draft, OCR-B, Roman, Sans Serif	Height	177 mm
Character sets	PCAPTEC, PC437, PC720, PC850, PC858, ISO 8859-15, Roman 8, Italic	Weight	8.37 kg
Number of characters	42	Packaging data	
Paper handling		Quantity per pack	1 pc(s)
Maximum print size	A3 (297 x 420 mm)	Package width	455 mm
Paper tray media types	Envelopes	Package depth	735 mm
Continuous paper thickness range	0.46 - 0.46 mm	Package height	300 mm
Label thickness range	0.46 - 0.46 mm	Package weight	12.1 kg
Multi-part paper thickness range	0.12 - 0.46 mm	Other features	
Single sheet thickness range	0.06 - 0.14 mm	Standard media sizes	Sheet Paper (single- and multi-layer), Continuous Paper (single- and multi-layer), Envelopes, Cardboard
Features		Connectivity technology	Wired
Product colour *	Black	Print technology	Dot matrix
Buffer size *	128 KB	Box contents	AC cable, Driver and utilities (CD), Ribbon, User guide
Sound pressure level (printing) *	55 dB	Needles	18 Needles (2 x 9)
Page description languages *	ESC P, PPDS	Technical details	
Country of origin	Indonesia	Sustainability certificates	ENERGY STAR
Ports & interfaces		Logistics data	
Standard interfaces *	Parallel, USB	Products per pallet	14 pc(s)
Endurance			
Print head *	9-pin		

Endurance		Logistics data	
Print direction	Bidirectional	Pallet gross weight	0 g
Print head life	400 million characters	Pallet gross length	120 cm
Ribbon life (black, draft)	12 million characters	Pallet gross width	80 cm
Print yield	12 characters	Pallet gross height	2.25 m
Mean time between failures (MTBF)	25000 h	Products per pallet layer	2 pc(s)
Power		Products per pallet layer (UK)	3 pc(s)
Power consumption (typical)	54 W	Products per pallet (UK)	21 pc(s)
Power consumption (standby)	8 W	Pallet weight (UK)	0 g
AC input voltage	198-264 V	Pallet length (UK)	120 cm
		Pallet width (UK)	100 cm
		Pallet height (UK)	2.25 m
		Harmonized System (HS) code	84433210



8715946645636

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 01-MAR-2025. Prints or copies of Information are only valid on the printed Publication date