D-Link GO-SW-5E/E verkkokytkin Hallitsematon Fast Ethernet (10/100) Valkoinen

Tuotemerkki : D-Link


Tuotekoodi: GO-SW-5E/E




Tuotteen nimi : GO-SW-5E/E


D-Link GO-SW-5E/E. Kytkin tyyppi: Hallitsematon. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Fast Ethernet (10/100), Basic kytkentä RJ-45 Ethernet-porttien määrä: 5. Täysin kaksipuolinen. MACosoitetaulukko: 2000 entries. Verkkostandardit: IEEE 802.3, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x. Virtaliitin: DC-tulo jakkiliitin

| Management features | | Weight & dimensions | |
|--|---|--|--------------------|
| Switch type * | Unmanaged | Width | 87 mm |
| Ports & interfaces | | Depth | 47.9 mm |
| Basic switching RJ-45 Ethernet ports guantity * | 5 | Height Packaging data | 21.7 mm |
| Basic switching RJ-45 Ethernet ports | Fast Ethernet (10/100) | Included power plug types | EU |
| Power connector | DC-in jack | Package width Package depth | 65 mm 105 mm |
| Network | | Package height | 98 mm |
| Networking standards * | IEEE 802.3, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x | Package weight | 150 g |
| 10G support * | X | Technical details | |
| Full duplex | × ✓ | Shipping (inner) case height | 23 cm |
| Auto MDI/MDI-X | · | Shipping (inner) case width | 35 cm |
| | | Shipping (inner) case length | 51.5 cm 7.5 kg |
| Data transmission | | Shipping (inner) case net weight Products per shipping (inner) case | 7.5 kg 50 pc(s) |
| MAC address table * Store-and-forward | 2000 entries | Pallet gross weight (air) | 405.2 kg |
| | • | Master (outer) cases per pallet (air) | 48 pc(s) |
| Design | | Products per pallet (air) | 2400 pc(s) |
| Rack mounting * | × | Pallet gross length | 110 cm |
| Stackable * | × | Pallet gross width | 120 cm |
| Product colour | White | Pallet height (air) | 197.5 cm |
| LED indicators | 1 | Pallet gross weight (sea) Master (outer) cases per pallet (sea) | 405.2 kg |
| Power over Ethernet (PoE) | | Products per pallet (sea) | 2400 pc(s) |
| Power over Ethernet (PoE) * | × | Pallet height (sea) | 197.5 cm |
| Other features | | Shipping (inner) case gross weight | 8 kg |
| Power LED | 1 | Logistics data | |
| Operational conditions | | Harmonized System (HS) code | 85176990 |
| Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) | 0 - 40 °C -10 - 70 °C 10 - 90% 5 - 90% | | |



7900693882620





790069388262

0790069388262

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.