D-Link

D-Link GO-SW-24G Hallitsematon L2 Gigabit Ethernet (10/100/1000) 1U musta

Tuotemerkki : D-Link　　　　　　　　　　**Tuotekoodi:** GO-SW-24G/E

Tuotteen nimi : GO-SW-24G

D-Link GO-SW-24G. Kytkin tyyppi: Hallitsematon, Kytkinkerros: L2. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 24. Täysin kaksipuolinen. MAC-osoitetaulukko: 8000 entries, Kytkentäkapasiteetti: 48 Gbit/s. Verkkostandardit: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x. Telineasennus, Kotelo: 1U

Management features	
Switch type *	Unmanaged
Switch layer	L2
Quality of Service (QoS) support	✔

Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity *	24
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)
Gigabit Ethernet (copper) ports quantity	24

Network	
Networking standards *	IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x
10G support *	✗
Copper ethernet cabling technology	1000BASE-T, 100BASE-TX, 10BASE-T
Full duplex	✔
Half duplex	✔
Flow control support	✔
Auto MDI/MDI-X	✔
Ethernet LAN data rates	10,100,1000 Mbit/s
Auto-negotiation	✔

Data transmission	
Switching capacity *	48 Gbit/s
Forwarding rate	35.71 Mpps
MAC address table *	8000 entries
Store-and-forward	✔
Number of queues	8
Jumbo frames support	✔
Jumbo frames	9216
Packet buffer memory	0.512 MB

Design	
Rack mounting *	✔
Form factor	1U
Product colour	Black
Housing material	Metal

Power	
Power consumption (max)	15.4 W

Power over Ethernet (PoE)	
Power over Ethernet (PoE) *	✗

Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 95%
Heat dissipation	52.54 BTU/h

Weight & dimensions	
Width	280 mm
Depth	180 mm
Height	44 mm
Weight	1.35 kg

Packaging data	
Package width	245 mm
Package depth	438 mm
Package height	77 mm
Package weight	2.3 kg

Technical details	
Shipping (inner) case height	27 cm
Shipping (inner) case width	41.3 cm
Shipping (inner) case length	46.3 cm
Shipping (inner) case net weight	11.5 kg
Products per shipping (inner) case	5 pc(s)
Pallet gross weight (air)	373.6 kg
Master (outer) cases per pallet (air)	28 pc(s)
Products per pallet (air)	140 pc(s)
Pallet gross length	110 cm
Pallet gross width	120 cm
Pallet height (air)	2.02 m
Pallet gross weight (sea)	373.6 kg
Master (outer) cases per pallet (sea)	28 pc(s)
Products per pallet (sea)	140 pc(s)
Pallet height (sea)	2.02 m
Shipping (inner) case gross weight	12.4 kg

Design

LED indicators	✔
Number of fans	0 fan(s)

Performance

Mean time between failures (MTBF)	302287 h

Power

Power supply included *	✔
Redundant power supply (RPS) support	✘
Number of power supply units	1
AC input voltage	100 - 240 V

Certificates

Certification	CE Class A, FCC Class A, VCCI Class A, BSMI, CCC UL, CB, LVD, BSMI, CCC

Logistics data

Harmonized System (HS) code	85176990

0790069396625

790069396625

7900693966252

5425656676686