



APC Smart-UPS SMT1500IC - 8x C13, USB, SmartConnect, 1500VA

Brand : APC

Product code: SMT1500IC

Product name : APC Smart-UPS SMT1500IC - 8x C13, USB, SmartConnect, 1500VA

APC Smart-UPS SMT1500IC - 8x C13, USB, SmartConnect, 1500VA

APC Smart-UPS SMT1500IC - 8x C13, USB, SmartConnect, 1500VA. UPS topology: Line-Interactive, Output power capacity: 1.5 kVA, Output power: 1000 W. AC outlet types: C13 coupler, IEC Jumpers, Power plug: C14 coupler, AC outlets quantity: 8 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 5 year(s), Battery recharge time: 3 h. Form factor: Mini Tower, Product colour: Black, Cable length: 1.83 m. Compliance certificates: RoHS, Certification: CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, UL 1778, VDE



Features		Battery	
UPS topology *	Line-Interactive	Automatic battery test	✓
Output power capacity *	1.5 kVA	Cold start	✓
Output power *	1000 W	Design	
Waveform *	Sine	Form factor *	Mini Tower
Input operation voltage (min) *	151 V	Cable length	1.83 m
Input operation voltage (max) *	302 V	Product colour *	Black
Input frequency *	50/60 Hz	Display type	LCD
Output operation voltage (min)	220 V	LED indicators	✓
Output operation voltage (max)	240 V	Operational conditions	
Output frequency	50/60 Hz	Operating temperature (T-T)	0 - 40 °C
Automatic Voltage Regulation (AVR)	✓	Storage temperature (T-T)	-15 - 45 °C
Surge energy rating	459 J	Operating relative humidity (H-H)	0 - 95%
Output voltage Total Harmonic Distortion (THD)	5%	Storage relative humidity (H-H)	0 - 95%
Noise level	45 dB	Operating altitude	0 - 3000 m
Surge protection	✓	Non-operating altitude	0 - 15000 m
Audible alarm(s)	✓	Certificates	
Web-based management	✓	Compliance certificates	RoHS
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm	Certification	CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, UL 1778, VDE
Auto-restart	✓	Packaging content	
Temperature voltage compensation	✓	Cables included	RS-232, USB cable
Ports & interfaces		Quick installation guide	✓
AC outlet types	C13 coupler, IEC Jumpers	Sustainability	
Power plug	C14 coupler	Sustainability certificates	Green Premium
AC outlets quantity	8 AC outlet(s)		

Ports & interfaces		Weight & dimensions	
USB port	✓	Width	171 mm
USB 2.0 ports quantity	1	Depth	439 mm
Serial interface	✓	Height	219 mm
Serial interface type	RS-232	Weight	24.1 kg
Serial ports quantity	1	Packaging data	
Ethernet LAN (RJ-45) ports	1	Resource CD	✓
SmartSlot	✓	Software CD	✓
Battery		Package width	328 mm
Battery technology	Sealed Lead Acid (VRLA)	Package depth	595 mm
Battery life (max)	5 year(s)	Package height	376 mm
Battery recharge time	3 h	Package weight	27.2 kg
Hot-swap battery	✓	Logistics data	
		Products per pallet	12 pc(s)
		Harmonized System (HS) code	85078000
		Total carbon footprint (kg of CO2e)	1270.81



0731304332992



731304332992

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.