



APC SMT1500IC UPS-virtalähde Linjainteraktiivinen 1,5 kVA 1000 W 8 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: SMT1500IC

Tuotteen nimi : SMT1500IC

APC SMT1500IC. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 1,5 kVA, Lähtöteho: 1000 W. Pistorasian tyypit: C13 liitin, IEC Jumpers, Virtapistoke: C14 liitin, Ulostulojen määrä: 8 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kestoikä (maks.): 5 vuosi/vuosia, Akun latausaika: 3 h. Kotelo: Mini Tower, Tuotteen väri: musta, Johdon pituus: 1,83 m. Vaatimustenmukaisuustodistukset: RoHS, Sertifointi: CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, UL 1778, VDE



Features		Battery	
UPS topology *	Line-Interactive	Automatic battery test	✓
Output power capacity *	1.5 kVA	Cold start	✓
Output power *	1000 W		
Waveform *	Sine		
Input operation voltage (min) *	151 V		
Input operation voltage (max) *	302 V		
Input frequency *	50/60 Hz		
Output operation voltage (min)	220 V		
Output operation voltage (max)	240 V		
Output frequency	50/60 Hz		
Automatic Voltage Regulation (AVR)	✓		
Surge energy rating	459 J		
Output voltage Total Harmonic Distortion (THD)	5%		
Noise level	45 dB		
Surge protection	✓		
Audible alarm(s)	✓		
Web-based management	✓		
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm		
Auto-restart	✓		
Temperature voltage compensation	✓		
Ports & interfaces		Design	
AC outlet types	C13 coupler, IEC Jumpers	Form factor *	Mini Tower
Power plug	C14 coupler	Cable length	1.83 m
AC outlets quantity	8 AC outlet(s)	Product colour *	Black
		Display type	LCD
		LED indicators	✓
		Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Storage temperature (T-T)	-15 - 45 °C
		Operating relative humidity (H-H)	0 - 95%
		Storage relative humidity (H-H)	0 - 95%
		Operating altitude	0 - 3000 m
		Non-operating altitude	0 - 15000 m
		Certificates	
		Compliance certificates	RoHS
		Certification	CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, UL 1778, VDE
		Packaging content	
		Cables included	RS-232, USB cable
		Quick installation guide	✓
		Sustainability	
		Sustainability certificates	Green Premium

Ports & interfaces		Weight & dimensions	
USB port	✓	Width	171 mm
USB 2.0 ports quantity	1	Depth	439 mm
Serial interface	✓	Height	219 mm
Serial interface type	RS-232	Weight	24.1 kg
Serial ports quantity	1	Packaging data	
Ethernet LAN (RJ-45) ports	1	Resource CD	✓
SmartSlot	✓	Software CD	✓
Battery		Package width	328 mm
Battery technology	Sealed Lead Acid (VRLA)	Package depth	595 mm
Battery life (max)	5 year(s)	Package height	376 mm
Battery recharge time	3 h	Package weight	27.2 kg
Hot-swap battery	✓	Logistics data	
		Products per pallet	12 pc(s)
		Harmonized System (HS) code	85078000
		Total carbon footprint (kg of CO2e)	1270.81



0731304332992



731304332992

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-APR-2025. Prints or copies of Information are only valid on the printed Publication date