

## APC Smart-UPS SMT1000RMI2UC - 4x C13, USB, Rackmount 2U, SmartConnect, 1000VA



Brand : APC Product code: SMT1000RMI2UC

**Product name :** APC Smart-UPS SMT1000RMI2UC - 4x C13, USB, Rackmount 2U, SmartConnect, 1000VA




APC Smart-UPS SMT750RMI2UC - 4x C13, USB, Rackmount 2U, SmartConnect, 750VA APC Smart-UPS SMT1000RMI2UC - 4x C13, USB, Rackmount 2U, SmartConnect, 1000VA. UPS topology: Line-Interactive, Output power capacity: 1 kVA, Output power: 700 W. AC outlet types: C13 coupler, AC outlets quantity: 4 AC outlet(s), USB port type: USB Type-A. Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 6 year(s), Battery recharge time: 3 h. Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Compliance certificates: RoHS, Certification: EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, UL 1778, VDE, REACH

Features		Battery	
UPS topology *	Line-Interactive	Replacement battery cartridge	APCRBC132
Output power capacity * 1 kVA Output power * 700 W Waveform * Sine Input operation voltage (min) * 151 V Input operation voltage (max) * 302 V Input frequency * 50/60 Hz Output operation voltage (min) 220 V Output operation voltage (max) 240 V Output frequency 50/60 Hz Automatic Voltage Regulation (AVR) ✓ Surge energy rating 459 J Response time 10 ms Output voltage Total Harmonic Distortion (THD)		Design	
	Sine 151 V 302 V 50/60 Hz 220 V	Form factor * Rack capacity Product colour * Display type LED indicators	Rackmount 2U Black LCD
		Operational conditions	
	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude	0 - 40 °C -15 - 45 °C 0 - 95% 0 - 95% 0 - 3000 m	
Noise level	45 dB	Non-operating altitude	0 - 15000 m
Surge protection	✓ ·	Certificates	
Web-based management	<b>✓</b>	Compliance certificates	RoHS
Auto-restart Temperature voltage compensation	<b>V</b>	Certification	EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, UL 1778, VDE, REACH
	•	Packaging content	
Ports & interfaces  AC outlet types  AC outlets quantity  USB port	C13 coupler 4 AC outlet(s)	Rack mount kit Cables included Quick installation guide	RS-232, USB cable
USB port type	USB Type-A	Sustainability	
Serial interface	<b>✓</b>	Sustainability certificates	Green Premium
Serial interface type	RJ-45	Weight & dimensions	
Ethernet LAN (RJ-45) ports SmartSlot	1	Width Depth	432 mm 477 mm
Battery		Height	86 mm
Battery technology	Sealed Lead Acid (VRLA)	Weight	22.5 kg
Number of batteries supported	1 6 year(s)	Packaging data	
Battery life (max) Battery recharge time	3 h	Resource CD	✓
Hot-swap battery	<b>✓</b>	Software CD	✓
Automatic battery test	· •	Package width	594 mm
Cold start	· •	Package depth	603 mm
		Package height Package weight	251 mm 31.4 kg

## Logistics data

Products per pallet 8 pc(s)
Harmonized System (HS) code 85078000
Total carbon footprint (kg of CO2e) 1165.17





731304332985

0731304332985

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.