



APC SMT1000RMI2UC UPS-virtalähde Linjainteraktiivinen 1 kVA 700 W 4 AC-pistorasia(a)



Tuotemerkki : APC

Tuotekoodi: SMT1000RMI2UC

Tuotteen nimi : SMT1000RMI2UC

APC SMT1000RMI2UC. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 1 kVA, Lähtöteho: 700 W. Pistorasian tyypit: C13 liitin, Ulostulojen määrä: 4 AC-pistorasia(a), USB-portin tyyppi: USB A-tyyppi. Akkuteknologia: Sealed Lead Acid (VRLA), Akun kestoikä (maks.): 6 vuosi/vuosia, Akun latausaika: 3 h. Kotelo: Telineasennettava, Tuotteen väri: musta, Telineen kapasiteetti: 2U. Vaatimustenmukaisuustodistukset: RoHS, Sertifointi: EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, UL 1778, VDE, REACH

Features		Battery	
UPS topology *	Line-Interactive	Replacement battery cartridge	APCRBC132
Output power capacity *	1 kVA	Design	
Output power *	700 W	Form factor *	Rackmount
Waveform *	Sine	Rack capacity	2U
Input operation voltage (min) *	151 V	Product colour *	Black
Input operation voltage (max) *	302 V	Display type	LCD
Input frequency *	50/60 Hz	LED indicators	✓
Output operation voltage (min)	220 V	Operational conditions	
Output operation voltage (max)	240 V	Operating temperature (T-T)	0 - 40 °C
Output frequency	50/60 Hz	Storage temperature (T-T)	-15 - 45 °C
Automatic Voltage Regulation (AVR)	✓	Operating relative humidity (H-H)	0 - 95%
Surge energy rating	459 J	Storage relative humidity (H-H)	0 - 95%
Response time	10 ms	Operating altitude	0 - 3000 m
Output voltage Total Harmonic Distortion (THD)	5%	Non-operating altitude	0 - 15000 m
Noise level	45 dB	Certificates	
Surge protection	✓	Compliance certificates	RoHS
Web-based management	✓	Certification	EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, UL 1778, VDE, REACH
Auto-restart	✓	Packaging content	
Temperature voltage compensation	✓	Rack mount kit	✓
Ports & interfaces		Cables included	RS-232, USB cable
AC outlet types	C13 coupler	Quick installation guide	✓
AC outlets quantity	4 AC outlet(s)	Sustainability	
USB port	✓	Sustainability certificates	Green Premium
USB port type	USB Type-A	Weight & dimensions	
Serial interface	✓	Width	432 mm
Serial interface type	RJ-45	Depth	477 mm
Ethernet LAN (RJ-45) ports	1	Height	86 mm
SmartSlot	✓	Weight	22.5 kg
Battery		Packaging data	
Battery technology	Sealed Lead Acid (VRLA)	Resource CD	✓
Number of batteries supported	1	Software CD	✓
Battery life (max)	6 year(s)	Package width	594 mm
Battery recharge time	3 h	Package depth	603 mm
Hot-swap battery	✓	Package height	251 mm
Automatic battery test	✓	Package weight	31.4 kg
Cold start	✓	Logistics data	
		Products per pallet	8 pc(s)

Logistics data

Harmonized System (HS) code	85078000
Total carbon footprint (kg of CO2e)	1165.17



0731304332985



731304332985

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.