



APC SMT1000IC UPS-virtalähde Linjainteraktiivinen 1 kVA 700 W 8 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: SMT1000IC

Tuotteen nimi : SMT1000IC

APC SMT1000IC. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 1 kVA, Lähtöteho: 700 W. Pistorasian tyypit: C13 liitin, IEC Jumpers, Virtapistoke: C14 liitin, Ulostulojen määrä: 8 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kestoikä (maks.): 5 vuosi/vuosia, Akun latausaika: 3 h. Kotelo: Mini Tower, Tuotteen väri: musta, Näytön tyyppi: LCD. Vaatimustenmukaisuustodistukset: RoHS, Sertifiointi: CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, UL 1778, VDE, REACH



Features		Battery	
UPS topology *	Line-Interactive	Hot-swap battery	✓
Output power capacity *	1 kVA	Automatic battery test	✓
Output power *	700 W	Cold start	✓
Waveform *	Sine	Replacement battery cartridge	RBC6
Input operation voltage (min) *	151 V	Design	
Input operation voltage (max) *	302 V	Form factor *	Mini Tower
Input frequency *	50/60 Hz	Product colour *	Black
Output operation voltage (min)	220 V	Display type	LCD
Output operation voltage (max)	240 V	LED indicators	✓
Output frequency	50/60 Hz	Operational conditions	
Automatic Voltage Regulation (AVR)	✓	Operating temperature (T-T)	0 - 40 °C
Surge energy rating	459 J	Storage temperature (T-T)	-15 - 45 °C
Response time	10 ms	Operating relative humidity (H-H)	0 - 95%
Output voltage Total Harmonic Distortion (THD)	5%	Storage relative humidity (H-H)	0 - 95%
Noise level	41 dB	Operating altitude	0 - 3000 m
Surge protection	✓	Non-operating altitude	0 - 15000 m
Audible alarm(s)	✓	Certificates	
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm	Compliance certificates	RoHS
Auto-restart	✓	Certification	CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, UL 1778, VDE, REACH
Temperature voltage compensation	✓	Packaging content	
Ports & interfaces		Cables included	RJ-45, USB cable
AC outlet types	C13 coupler, IEC Jumpers	Quick installation guide	✓
Power plug	C14 coupler		
AC outlets quantity	8 AC outlet(s)		
USB port	✓		

Ports & interfaces		Sustainability	
USB 2.0 ports quantity	1	Sustainability certificates	Green Premium
USB port type	USB Type-A	Weight & dimensions	
Serial interface	✓	Width	171 mm
Serial ports quantity	1	Depth	439 mm
Ethernet LAN (RJ-45) ports	1	Height	219 mm
SmartSlot	✓	Weight	18.9 kg
Battery		Packaging data	
Battery technology	Sealed Lead Acid (VRLA)	Package width	328 mm
Battery life (max)	5 year(s)	Package depth	595 mm
Battery recharge time	3 h	Package height	376 mm
		Package weight	22.8 kg
		Logistics data	
		Products per pallet	12 pc(s)
		Harmonized System (HS) code	85078000
		Total carbon footprint (kg of CO2e)	984.74



0731304332978



731304332978

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-APR-2025. Prints or copies of Information are only valid on the printed Publication date