

## APC SMC1500IC UPS-virtalähde Linjainteraktiivinen 1,5 kVA 900 W 8 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: SMC1500IC

Tuotteen nimi : SMC1500IC

APC SMC1500IC. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 1,5 kVA, Lähtöteho: 900 W. Pistorasian tyypit: C13 liitin, Virtapistoke: C14 liitin, Ulostulojen määrä: 8 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kestoikä (maks.): 5 vuosi/vuosia, Akun latausaika: 3 h. Kotelo: Mini Tower, Tuotteen väri: musta, Näytön tyyppi: LCD. Sertifiointi: C-tick, CE, CSA, GOST, UL 1778, VDE





| Features  |  | Battery  |   |
|---|--|--|---|
| UPS topology *<br>Output power capacity *<br>Output power *   | Line-Interactive<br>1.5 kVA<br>900 W   | Hot-swap battery<br>Automatic battery test<br>Cold start   | 4<br>4<br>4   |
| Waveform *<br>Input operation voltage (min) *<br>Input operation voltage (max) *<br>Input frequency *<br>Output operation voltage (min)<br>Output operation voltage (max)                     | Sine<br>170 V<br>300 V<br>50/60 Hz<br>220 V<br>240 V   | Design<br>Form factor *<br>Product colour *<br>Display type<br>LED indicators  | Mini Tower<br>Black<br>LCD  |
| Output frequency<br>Automatic Voltage Regulation (AVR)<br>Surge energy rating<br>Output voltage Total Harmonic<br>Distortion (THD)<br>Noise level<br>Audible alarm(s)<br>Web-based management | 50/60 Hz<br>459 J<br>5%<br>45 dB<br>4  | Operational conditions<br>Operating temperature (T-T)<br>Storage temperature (T-T)<br>Operating relative humidity (H-H)<br>Storage relative humidity (H-H)<br>Operating altitude<br>Non-operating altitude | 0 - 40 °C<br>-15 - 45 °C<br>0 - 95%<br>0 - 95%<br>0 - 3000 m<br>0 - 15000 m |
| Audible alarm modes<br>Auto-restart<br>Temperature voltage compensation   | Alarm when on battery, Low battery<br>alarm, Overload alarm<br></td <td>Certificates Certification Packaging content</td> <td>C-tick, CE, CSA, GOST, UL 1778,<br/>VDE</td> | Certificates Certification Packaging content   | C-tick, CE, CSA, GOST, UL 1778,<br>VDE                                      |
| Ports & interfaces<br>AC outlet types<br>Power plug<br>AC outlets quantity<br>USB port  | C13 coupler<br>C14 coupler<br>8 AC outlet(s)   | Cables included Sustainability Sustainability certificates   | USB cable<br>Green Premium  |

| Ports & interfaces            |                         | Weight & dimensions |                       |
|-------------------------------|-------------------------|---------------------|-----------------------|
| USB 2.0 ports quantity        | 1                       | Width               | 171 mm                |
| Serial interface              | 1                       | Depth               | 439 mm                |
| Serial ports quantity         | 1                       | Height              | 219 mm                |
| Battery                       |                         | Weight              | 24.1 kg               |
| Battery technology            | Sealed Lead Acid (VRLA) | Packaging data      |                       |
| Number of batteries supported | 1                       | Resource CD         | ✓                     |
| Battery life (max)            | 5 year(s)               | Software CD         | ✓                     |
| Battery recharge time         | 3 h                     | Package width       | 328 mm                |
|                               |                         | Package depth       | 595 mm                |
|                               |                         | Package height      | 376 mm                |
|                               |                         | Package volume      | 27230 cm <sup>3</sup> |

## Logistics data

| Products per pallet                 | 18 pc(s) |
|-------------------------------------|----------|
| Harmonized System (HS) code         | 85078000 |
| Total carbon footprint (kg of CO2e) | 1090.81  |





731304332961

0731304332961

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.