

APC SMC1500I-2UC UPS-virtalähde Linjainteraktiivinen 1,5 kVA 900 W 4 AC-pistorasia(a)



Tuotemerkki : APC Tuotekoodi: SMC1500I-2UC

Tuotteen nimi: SMC1500I-2UC



APC SMC1500I-2UC. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 1,5 kVA, Lähtöteho: 900 W. Pistorasian tyypit: C13 liitin, Virtapistoke: C14 liitin, Ulostulojen määrä: 4 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kestoikä (maks.): 6 vuosi/vuosia, Akun latausaika: 3 h. Kotelo: Telineasennettava, Tuotteen väri: musta, Telineen kapasiteetti: 2U. Tuotteen leveys: 432 mm, Tuotteen syvyys: 477 mm, Tuotteen korkeus: 86 mm

Eastures		Pottom	
Features		Battery	
UPS topology *	Line-Interactive 1.5 kVA	Hot-swap battery	1
Output power capacity * Output power *	900 W	Automatic battery test	✓
Waveform *	Sine	Cold start	✓
Input operation voltage (min) *	170 V	Design	
Input operation voltage (max) *	300 V	Form factor *	Rackmount
Input frequency *	50/60 Hz	Rack capacity	2U
Output operation voltage (min)	220 V	Product colour *	Black
Output operation voltage (max)	240 V	Display type	LCD
Output frequency	50/60 Hz	LED indicators	✓
Automatic Voltage Regulation (AVR)	✓	Certification	C-tick, CE, CSA, GOST, UL 1778,
Surge energy rating	459 J	Certification	VDE
Output voltage Total Harmonic Distortion (THD)	5%	Operational conditions	0 - 40 °C
Noise level	46 dB	Operating temperature (T-T) Storage temperature (T-T)	-15 - 45 °C
Audible alarm(s)	✓	Operating relative humidity (H-H)	0 - 95%
Web-based management	✓	Storage relative humidity (H-H)	0 - 95%
Audible alarm modes	Alarm when on battery, Low battery	Operating altitude	0 - 3000 m
Auto-restart	alarm, Overload alarm	Non-operating altitude	0 - 15000 m
Temperature voltage compensation	•	Technical details	
	•	Sustainability certificates	Green Premium
Ports & interfaces	010	Weight & dimensions	
AC outlet types	C13 coupler	Width	432 mm
Power plug AC outlets quantity	C14 coupler 4 AC outlet(s)	Depth	477 mm
• •	✓ AC outlet(s)	Height	86 mm
USB port		Weight	28.6 kg
USB 2.0 ports quantity	1	Package width	594 mm
Serial interface	V	Package depth	603 mm
Serial interface type	RJ-45	Package height	251 mm
Battery		Package weight	31.9 kg
Battery technology Battery life (max) Battery recharge time	Sealed Lead Acid (VRLA) 6 year(s) 3 h	Packaging data	
		Rack mount kit	✓
		Cables included	USB cable
		Quick installation guide	✓
		Resource CD	✓
		Software CD	✓
		Logistics data	
		Products per pallet	16 pc(s)
		Harmonized System (HS) code	85078000





731304332954

0731304332954

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.