![APC]

APC Smart-UPS C, Line Interactive, 1000VA, Tower, 230V, 8x IEC C13 outlets, SmartConnect port, USB and Serial communication, AVR, Graphic LCD

Brand : APC

Product name : Smart-UPS C, Line Interactive, 1000VA, Tower, 230V, 8x IEC C13 outlets, SmartConnect port, USB and Serial communication, AVR, Graphic LCD

Product code: SMC1000IC

- 1000VA/600W line interactive pure sine wave tower UPS
- Ideal for entry-level servers, networks, retail POS, business VOIP and desktops
- Automatic Voltage Regulation keeps output voltage within acceptable user selectable levels
- Cloud-based remote power monitoring via SmartConnect Ethernet Port
- Graceful shutdown using serial or USB cables via PowerChute Serial Shutdown
Smart-UPS C, Line Interactive, 1000VA, Tower, 230V, 8x IEC C13 outlets, SmartConnect port, USB and Serial communication, AVR, Graphic LCD

Features

UPS topology *	Line-Interactive
Output power capacity *	1 kVA
Output power *	600 W
Waveform *	Sine
Input operation voltage (min) *	170 V
Input operation voltage (max) *	300 V
Input frequency *	50/60 Hz
Output operation voltage (min)	220 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Automatic Voltage Regulation (AVR)	✔
Surge energy rating	455 J
Output voltage Total Harmonic Distortion (THD)	5%
Noise level	41 dB
Surge protection	✔
Audible alarm(s)	✔
Web-based management	✔
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm
Auto-restart	✔
Temperature voltage compensation	✔

Ports & interfaces

AC outlet types	C13 coupler
Power plug	C14 coupler
AC outlets quantity	8 AC outlet(s)

Battery

Hot-swap battery	✔
Automatic battery test	✔
Cold start	✔

Design

Form factor *	Mini Tower
Product colour *	Black
Display type	LCD
LED indicators	✔

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m

Certificates

Certification	CE, CSA, GOST, UL 1778, VDE

Packaging content

Cables included	USB cable

Sustainability

Sustainability certificates	Green Premium

Weight & dimensions

Width	171 mm

Ports & interfaces

USB port	✔
USB 2.0 ports quantity	1
Serial ports quantity	1
Ethernet LAN (RJ-45) ports	1

Battery

Battery technology	Sealed Lead Acid (VRLA)
Battery life (max)	5 year(s)
Battery recharge time	3 h

Weight & dimensions

Depth	439 mm
Height	219 mm
Weight	17.3 kg

Packaging data

Resource CD	✔
Software CD	✔
Package width	328 mm
Package depth	595 mm
Package height	376 mm
Package weight	19.6 kg

Logistics data

Products per pallet	18 pc(s)
Harmonized System (HS) code	85078000
Total carbon footprint (kg of CO2e)	853.59

0731304332947

731304332947