



APC Smart-UPS UPS-virtalähde Linjainteraktiivinen 3 kVA 2700 W 9 AC-pistorasia(a)



Tuotemerkki : APC

Tuotekoodi: SMX3000RMHV2UNC

Tuotteen nimi : Smart-UPS

APC Smart-UPS. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 3 kVA, Lähtöteho: 2700 W. Pistorasian tyypit: C13 liitin, C19 liitin, Virtapistoke: C20 liitin, Ulostulojen määrä: 9 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 738 VAh, Tyypillinen varmuuskopioaika täydellä kuormituksella: 6,25 min. Kotelo: Telineasennettava/Torni, Tuotteen väri: musta, Telineen kapasiteetti: 2U. Vaatimustenmukaisuustodistukset: RoHS, Sertifiointi: C-tick, CE, EN 50091-1, EN 50091-2, EN 55022 Class A, EN 60950, FCC Part 15 Class A, GOST, IRAM,...

Features		Design	
UPS topology *	Line-Interactive	Product colour *	Black
Output power capacity *	3 kVA	LED indicators	Battery replacement
Output power *	2700 W	Operational conditions	
Waveform *	Sine	Operating temperature (T-T)	0 - 40 °C
Input frequency *	50/60 Hz	Storage temperature (T-T)	-15 - 45 °C
Output operation voltage (min)	208 V	Operating relative humidity (H-H)	0 - 95%
Output operation voltage (max)	240 V	Storage relative humidity (H-H)	0 - 95%
Output frequency regulation	50/60 Hz	Operating altitude	0 - 3000 m
Automatic Voltage Regulation (AVR)	✓	Non-operating altitude	0 - 15000 m
Surge energy rating	645 J	Certificates	
Hold time (min)	2 ms	Compliance certificates	RoHS
Hold time (max)	10 ms	Certification	C-tick, CE, EN 50091-1, EN 50091-2, EN 55022 Class A, EN 60950, FCC Part 15 Class A, GOST, IRAM, UL 1778, VDE, REACH, PEP, EOLI
Efficiency	98.5%	Packaging content	
Emergency Power Off (EPO)	✓	Rack mount kit	✓
Noise level	55 dB	Cables included	RS-232
Surge protection	✓	Manual	✓
Audible alarm(s)	✓	Sustainability	
Auto-restart	✓	Sustainability certificates	Green Premium
Ports & interfaces		Weight & dimensions	
AC outlet types	C13 coupler, C19 coupler	Width	432 mm
Power plug	C20 coupler	Depth	667 mm
AC outlets quantity	9 AC outlet(s)	Height	85 mm
Number of output IEC jumpers	2	Weight	37.3 kg
SmartSlot	✓	Packaging data	
Battery		Temperature sensor	✓
Battery technology	Sealed Lead Acid (VRLA)	Software CD	✓
Battery capacity	738 VAh	Package width	596 mm
Typical backup time at full load	6.25 min	Package depth	869 mm
Typical backup time at half load	18 min	Package height	85 mm
Battery life (max)	5 year(s)	Package weight	45.4 kg
Battery recharge time	3 h	Logistics data	
Hot-swap battery	✓	Products per pallet	8 pc(s)
Automatic battery test	✓	Harmonized System (HS) code	85078000
Design		Total carbon footprint (kg of CO2e)	2723.74
Form factor *	Rackmount/Tower	Other features	
Rack capacity	2U	Nominal output voltage	230 V
Cable length	2.44 m	Nominal input voltage	230 V

Other features

Packaging content

Web/SNMP Management Card



0731304272694



731304272694

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.