



## APC Smart-UPS UPS-virtalähde Linjainteraktiivinen 3 kVA 2700 W 10 AC-pistorasia(a)



**Tuotemerkki :** APC

**Tuotekoodi:** SMX3000HV

**Tuotteen nimi :** Smart-UPS

APC Smart-UPS. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 3 kVA, Lähtöteho: 2700 W. Pistorasian tyypit: C13 liitin, C19 liitin, Virtapistoke: C20 liitin, Ulostulojen määrä: 10 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 738 VAh, Tyypillinen varmuuskopioaika täydellä kuormituksella: 6,25 min. Kotelo: Telineasennettava/Torni, Tuotteen väri: musta, Ruostumaton teräs, Telineen kapasiteetti: 4U. Tuotteen leveys: 178 mm, Tuotteen syvyys: 483 mm, Tuotteen korkeus: 432 mm

Features		Battery	
UPS topology *	Line-Interactive	Automatic battery test	✓
Output power capacity *	3 kVA	<b>Design</b>	
Output power *	2700 W	Form factor *	Rackmount/Tower
Waveform *	Sine	Rack capacity	4U
Input operation voltage (min) *	140 V	Cable length	1.83 m
Input operation voltage (max) *	280 V	Product colour *	Black, Stainless steel
Input frequency *	50/60 Hz	Display type	LCD
Output operation voltage (min)	208 V	LED indicators	Status
Output operation voltage (max)	240 V	Certification	C-tick, CE, CSA, EN 50091-1, EN 50091-2, EN 60950, FCC Part 15 Class A, GOST, IRAM, UL 1778, VDE, REACH
Output frequency regulation	50/60 Hz	<b>Operational conditions</b>	
Automatic Voltage Regulation (AVR) ✓		Operating temperature (T-T)	0 - 40 °C
Surge energy rating	645 J	Storage temperature (T-T)	-15 - 45 °C
Hold time (min)	2 ms	Operating relative humidity (H-H)	0 - 95%
Hold time (max)	10 ms	Storage relative humidity (H-H)	0 - 95%
Efficiency	98.5%	Operating altitude	0 - 3000 m
Crest factor	3:1	Non-operating altitude	0 - 15000 m
Emergency Power Off (EPO) ✓		<b>Technical details</b>	
Noise level	55 dB	Compliance certificates	RoHS
Surge protection ✓		<b>Weight &amp; dimensions</b>	
Audible alarm(s) ✓		Width	178 mm
Auto-restart ✓		Depth	483 mm
<b>Ports &amp; interfaces</b>		Height	432 mm
AC outlet types	C13 coupler, C19 coupler	Weight	38.6 kg
Power plug	C20 coupler	Package width	586 mm
AC outlets quantity	10 AC outlet(s)	Package depth	633 mm
Number of output IEC jumpers	2	Package height	330 mm
SmartSlot ✓		Package weight	47.7 kg
<b>Battery</b>			
Battery technology	Sealed Lead Acid (VRLA)		
Battery capacity	738 VAh		

Battery		Packaging data	
Typical backup time at full load	6.25 min	Rack mount kit	✓
Typical backup time at half load	18 min	Cables included	RS-232, USB cable
Battery life (max)	5 year(s)	Manual	✓
Battery recharge time	3 h	Quick installation guide	✓
Hot-swap battery	✓	Software CD	✓
		Logistics data	
		Products per pallet	6 pc(s)
		Harmonized System (HS) code	85078000
		Other features	
		Nominal output voltage	230 V



0731304292616



731304292616

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.