

APC Smart-UPS UPS-virtalähde Linjainteraktiivinen 1,5 kVA 1200 W 8 AC-pistorasia(a)

Tuotemerkki : APC Tuotekoodi: SMX1500RMI2UNC

Tuotteen nimi: Smart-UPS



APC Smart-UPS. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 1,5 kVA, Lähtöteho: 1200 W. Pistorasian tyypit: C13 liitin, Virtapistoke: C14 liitin, Ulostulojen määrä: 8 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 311 VAH, Tyypillinen varmuuskopioaika täydellä kuormituksella: 5,8 min. Kotelo: Telineasennettava/Torni, Tuotteen väri: musta, Telineen kapasiteetti: 2U. Vaatimustenmukaisuustodistukset: RoHS, Sertifiointi: C-tick, CE, EN 50091-1, EN 50091-2, VDE, REACH, PEP, EOLI



Features		Design	
UPS topology * Line-Interactive Output power capacity * 1.5 kVA Output power * 1200 W Waveform * Sine Input operation voltage (min) * 151 V	Rack capacity Cable length Product colour * Display type LED indicators	2U 1.83 m Black LCD	
Input operation voltage (max) * Input frequency * Output frequency regulation Automatic Voltage Regulation (AVR) Surge energy rating Efficiency Emergency Power Off (EPO)	302 V 50/60 Hz 50/60 Hz √R) ✓ 645 J 98.5% ✓ 40 dB ✓ Low battery alarm, Overload alarm	Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude	0 - 40 °C -15 - 45 °C 0 - 95% 0 - 95% 0 - 3000 m
Noise level Surge protection Audible alarm(s) Audible alarm modes		Non-operating altitude Certificates Compliance certificates Certification	0 - 15000 m RoHS C-tick, CE, EN 50091-1, EN 50091-2, VDE, REACH, PEP, EOLI
Auto-restart Ports & interfaces	✓	Packaging content	
C outlet types C13 coupler ower plug C14 coupler C outlets quantity 8 AC outlet(s)	Rack mount kit Cables included Quick installation guide	RS-232, USB cable	
Number of output IEC jumpers	2	Weight & dimensions	
USB port SmartSlot	/	Width Depth	432 mm 490 mm 89 mm
Battery Battery technology Battery capacity	Sealed Lead Acid (VRLA) 311 VAh	Height Weight	24.8 kg

Battery		Packaging data	
Typical backup time at full load	5.8 min	Software CD	✓
Typical backup time at half load	17.2 min	Package width	589 mm
Battery life (max)	5 year(s)	Package depth	620 mm
Battery recharge time	3 h	Package height	246 mm
Hot-swap battery	✓	Package weight	30 kg
Automatic battery test	✓	Logistics data	
Cold start	✓	Products per pallet	8 pc(s)
Design		Harmonized System (HS) code	85078000
Form factor *	Rackmount/Tower	Total carbon footprint (kg of CO2e)	1419.64
		Other features	
		Nominal output voltage	230 V
		Nominal input voltage	230 V
		Packaging content	Removable support feet





731304281702

0731304281702

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.