



APC SMX1000I

Tuotemerkki : APC

Tuotekoodi: SMX1000I

Tuotteen nimi : SMX1000I

Smart-UPS X 1000VA LCD line-interactive UPS, räkki/tornimalli
APC SMX1000I. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 1 kVA, Lähtöteho: 800 W. Pistorasian tyypit: C13 liitin, Virtapistoke: C14 liitin, Ulostulojen määrä: 8 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 299 VAh, Tyypillinen varmuuskopioaika täydellä kuormituksella: 8,1 min. Kotelo: Telineasennettava/Torni, Tuotteen väri: musta, Telineen kapasiteetti: 2U. Vaatimustenmukaisuustodistukset: RoHS, Sertifiointi: CE, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE, REACH, PEP, EOL



| Features | | Design | |
|------------------------------------|-----------------------------------|-----------------------------------|---|
| UPS topology * | Line-Interactive | Cable length | 1.83 m |
| Output power capacity * | 1 kVA | Product colour * | Black |
| Output power * | 800 W | LED indicators | ✓ |
| Waveform * | Sine | Operational conditions | |
| Input operation voltage (min) * | 151 V | Operating temperature (T-T) | 0 - 40 °C |
| Input operation voltage (max) * | 302 V | Storage temperature (T-T) | -15 - 45 °C |
| Input frequency * | 50/60 Hz | Operating relative humidity (H-H) | 0 - 95% |
| Output frequency regulation | 50/60 Hz | Storage relative humidity (H-H) | 0 - 95% |
| Automatic Voltage Regulation (AVR) | ✓ | Operating altitude | 0 - 3000 m |
| Surge energy rating | 600 J | Non-operating altitude | 0 - 15000 m |
| Efficiency | 98.2% | Certificates | |
| Emergency Power Off (EPO) | ✓ | Compliance certificates | RoHS |
| Noise level | 40 dB | Certification | CE, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE, REACH, PEP, EOL |
| Surge protection | ✓ | Packaging content | |
| Audible alarm(s) | ✓ | Rack mount kit | ✓ |
| Audible alarm modes | Low battery alarm, Overload alarm | Cables included | RS-232, USB cable |
| Auto-restart | ✓ | Quick installation guide | ✓ |
| Ports & interfaces | | Sustainability | |
| AC outlet types | C13 coupler | Sustainability certificates | Green Premium |
| Power plug | C14 coupler | Weight & dimensions | |
| AC outlets quantity | 8 AC outlet(s) | Width | 432 mm |
| Number of output IEC jumpers | 2 | Depth | 490 mm |
| USB port | ✓ | Height | 89 mm |
| SmartSlot | ✓ | Weight | 22.9 kg |
| Battery | | | |
| Battery technology | Sealed Lead Acid (VRLA) | | |
| Battery capacity | 299 VAh | | |

| Battery | | Packaging data | |
|----------------------------------|-----------------|-------------------------------------|------------------------|
| Typical backup time at full load | 8.1 min | Software CD | ✓ |
| Typical backup time at half load | 24.2 min | Package width | 589 mm |
| Battery life (max) | 5 year(s) | Package depth | 620 mm |
| Battery recharge time | 3 h | Package height | 246 mm |
| Hot-swap battery | ✗ | Package weight | 27.3 kg |
| Automatic battery test | ✓ | Logistics data | |
| Cold start | ✓ | Products per pallet | 8 pc(s) |
| Design | | Harmonized System (HS) code | 85078000 |
| Form factor * | Rackmount/Tower | Total carbon footprint (kg of CO2e) | 1153.31 |
| Rack capacity | 2U | Other features | |
| | | Nominal output voltage | 230 V |
| | | Nominal input voltage | 230 V |
| | | Packaging content | Removable support feet |



0731304268635



731304268635

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-APR-2025. Prints or copies of Information are only valid on the printed Publication date