



## APC Smart-UPS SMT750RMI2UNC - 4x C13, USB, Rack mountable, NMC, 750VA

Brand : APC

Product code: SMT750RMI2UNC

Product name : APC Smart-UPS SMT750RMI2UNC - 4x C13, USB, Rack mountable, NMC, 750VA



APC Smart-UPS SMT750RMI2UNC - 4x C13, USB, Rack mountable, NMC, 750VA

APC Smart-UPS SMT750RMI2UNC - 4x C13, USB, Rack mountable, NMC, 750VA. UPS topology: Line-Interactive, Output power capacity: 0.75 kVA, Output power: 500 W. AC outlet types: C13 coupler, C14 coupler, Power plug: C14 coupler, AC outlets quantity: 4 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 168 Ah, Battery recharge time: 3 h. Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Compliance certificates: RoHS, Certification: CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE

Features		Design	
UPS topology *	Line-Interactive	Rack capacity	2U
Output power capacity *	0.75 kVA	Product colour *	Black
Output power *	500 W	Display type	LCD
Waveform *	Sine	LED indicators	✓
Input operation voltage (min) *	151 V	<b>Operational conditions</b>	
Input operation voltage (max) *	302 V	Operating temperature (T-T)	0 - 40 °C
Input frequency *	50/60 Hz	Storage temperature (T-T)	-15 - 45 °C
Output operation voltage (min)	220 V	Operating relative humidity (H-H)	0 - 95%
Output operation voltage (max)	240 V	Storage relative humidity (H-H)	0 - 95%
Output frequency	50/60 Hz	Operating altitude	0 - 3000 m
Output frequency regulation	+/- 3 Hz	Non-operating altitude	0 - 15000 m
Output voltage regulation	5%	<b>Certificates</b>	
Surge energy rating	459 J	Compliance certificates	RoHS
Response time	2 ms	Certification	CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE
Emergency Power Off (EPO)	0	<b>Packaging content</b>	
Noise level	46 dB	Rack mount kit	✓
Surge protection	✓	Cables included	Input power cable, USB cable
Audible alarm(s)	✓	Quick installation guide	✓
Web-based management	✓	<b>Sustainability</b>	
Audible alarm modes	Battery replacement	Sustainability certificates	Green Premium
Auto-restart	✓	<b>Weight &amp; dimensions</b>	
<b>Ports &amp; interfaces</b>		Width	432 mm
AC outlet types	C13 coupler, C14 coupler	Depth	406 mm
Power plug	C14 coupler	Height	89 mm
AC outlets quantity	4 AC outlet(s)	Weight	17.2 kg
USB 2.0 ports quantity	1	<b>Packaging data</b>	
Ethernet LAN (RJ-45) ports	1	Resource CD	✓
<b>Battery</b>		Package width	546 mm
Battery technology	Sealed Lead Acid (VRLA)	Package depth	584 mm
Battery capacity	168 Ah	Package height	241 mm
Battery recharge time	3 h	Package weight	21.2 kg
Hot-swap battery	✓		
Automatic battery test	✓		
Cold start	✓		

**Design**

Form factor \* Rackmount

**Logistics data**


Products per pallet	16 pc(s)
Harmonized System (HS) code	85078000
Total carbon footprint (kg of CO2e)	497.38

**Other features**

Output voltage	230 V
----------------	-------



0731304327721



731304327721

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.