

## APC Smart-UPS 750VA UPS-virtalähde Linjainteraktiivinen 0,75 kVA 500 W 4 AC-pistorasia(a)

Tuotemerkki : APC Tuotekoodi: SMT750RMI2UNC

Tuotteen nimi: Smart-UPS 750VA




APC Smart-UPS 750VA. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 0,75 kVA, Lähtöteho: 500 W. Pistorasian tyypit: C13 liitin, C14 liitin, Virtapistoke: C14 liitin, Ulostulojen määrä: 4 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 168 ah, Akun latausaika: 3 h. Kotelo: Telineasennettava, Tuotteen väri: musta, Telineen kapasiteetti: 2U. Vaatimustenmukaisuustodistukset: RoHS, Sertifiointi: CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, GS

Mark, IRAM, RCM, VDE, WEEE



Features		Design	
UPS topology * Line-Interactive Output power capacity * 0.75 kVA Output power * 500 W Waveform * Sine Input operation voltage (min) * 151 V Input operation voltage (max) * 302 V Input frequency * 50/60 Hz Output operation voltage (min) 220 V Output operation voltage (max) 240 V Output operation voltage (max) 240 V Output frequency 50/60 Hz Output frequency regulation +/- 3 Hz Output voltage regulation 5% Surge energy rating 459 J Response time 2 ms Emergency Power Off (EPO) O Noise level 46 dB	0.75 kVA 500 W Sine 151 V	Rack capacity Product colour * Display type LED indicators	2U Black LCD
		Operational conditions	
	50/60 Hz 220 V 240 V 50/60 Hz +/- 3 Hz	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	0 - 40 °C -15 - 45 °C 0 - 95% 0 - 95% 0 - 3000 m 0 - 15000 m
		Certificates	
	0	Compliance certificates  Certification	RoHS CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE
Surge protection Audible alarm(s)	· ·	Packaging content	
Web-based management  ✓ Audible alarm modes  Battery replacement  ✓  ✓  ✓  ✓  ✓  ✓  ✓  ✓  ✓  ✓  ✓  ✓  ✓	Battery replacement	Rack mount kit Cables included Quick installation guide	✓ Input power cable, USB cable ✓
Ports & interfaces		Sustainability	
AC outlet types	C13 coupler, C14 coupler	Sustainability certificates	Green Premium
ower plug C14 coupler C outlets quantity 4 AC outlet(s) SB 2.0 ports quantity 1 thernet LAN (RJ-45) ports 1 attery	4 AC outlet(s) 1	Weight & dimensions Width Depth Height Weight	432 mm 406 mm 89 mm 17.2 kg
Battery technology	Sealed Lead Acid (VRLA)	Packaging data	
Battery capacity Battery recharge time Hot-swap battery Automatic battery test Cold start	ery recharge time 3 h swap battery  matic battery test	Resource CD Package width Package depth Package height Package weight	546 mm 584 mm 241 mm 21.2 kg

Design		Logistics data	
Form factor *	Rackmount	Products per pallet	16 pc(s)
		Harmonized System (HS) code	85078000
		Total carbon footprint (kg of CO2e)	497.38
		Other features	
		Output voltage	230 V





731304327721

0731304327721

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.