



## APC Smart-UPS On-Line UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 6 kVA 6000 W 10 AC-pistorasia(a)

**Tuotemerkki :** APC

**Tuotekoodi:** SRT6KXLI

**Tuotteen nimi :** Smart-UPS On-Line

APC Smart-UPS On-Line. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 6 kVA, Lähtöteho: 6000 W. Pistorasian tyypit: C13 liitin, C19 liitin, Virtapistoke: Hardwire, Ulostulojen määrä: 10 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 902 VAH, Tyypillinen varmuuskopioaika täydellä kuormituksella: 2,5 min. Kotelo: Telineasennettava/Torni, Tuotteen väri: musta, Näytön tyyppi: LCD. Vaatimustenmukaisuustodistukset: RoHS, Sertifiointi: REACH, CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, IRAM, RCM, VDE



Features		Design	
UPS topology *	Double-conversion (Online)	Form factor *	Rackmount/Tower
Output power capacity *	6 kVA	Product colour *	Black
Output power *	6000 W	Display type	LCD
Waveform *	Sine	LED indicators	Status
Input operation voltage (min) *	100 V	International Protection (IP) code	IP20
Input operation voltage (max) *	275 V		
Input frequency *	40 - 70 Hz		
Output operation voltage (min)	220 V		
Output operation voltage (max)	240 V		
Output frequency regulation	50/60 Hz		
Surge energy rating	480 J		
Number of output phases	1		
Efficiency	94.4%		
Crest factor	3:1		
Emergency Power Off (EPO)	✓		
Output voltage Total Harmonic Distortion (THD)	3%		
Noise level	55 dB		
Surge protection	✓		
Audible alarm(s)	✓		
Auto-restart	✓		
Ports & interfaces		Operational conditions	
AC outlet types	C13 coupler, C19 coupler	Operating temperature (T-T)	0 - 40 °C
		Storage temperature (T-T)	-15 - 45 °C
		Operating relative humidity (H-H)	0 - 95%
		Storage relative humidity (H-H)	0 - 95%
		Operating altitude	0 - 3000 m
		Non-operating altitude	0 - 15000 m
		Certificates	
		Compliance certificates	RoHS
		Certification	REACH, CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, IRAM, RCM, VDE
		Packaging content	
		Cables included	USB cable
		Quick installation guide	✓
		Sustainability	
		Sustainability certificates	ENERGY STAR

Ports & interfaces		Weight & dimensions	
Power plug	Hardwire	Width	174 mm
AC outlets quantity	10 AC outlet(s)	Depth	719 mm
Number of output IEC jumpers	2	Height	432 mm
USB port	✓	Weight	60 kg
Serial interface	✓	<b>Packaging data</b>	
Serial interface type	RJ-45	Temperature sensor	✓
SmartSlot	✓	Warranty card	✓
<b>Battery</b>		Software CD	✓
Battery technology	Sealed Lead Acid (VRLA)	Package width	610 mm
Battery capacity	902 VAh	Package depth	960 mm
Typical backup time at full load	2.5 min	Package height	370 mm
Typical backup time at half load	8.7 min	Package weight	67 kg
Battery life (max)	5 year(s)	<b>Logistics data</b>	
Battery recharge time	1.5 h	Products per pallet	6 pc(s)
Hot-swap battery	✓	Harmonized System (HS) code	85078000
Automatic battery test	✓	Total carbon footprint (kg of CO2e)	13539.46
Cold start	✓	<b>Other features</b>	
		Packaging content	Removable support feet Web/SNMP Management Card



0731304301660



731304301660

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.