



APC SUVTP10KH4B4S uninterruptible power supply (UPS) 10 kVA 8000 W

Brand : APC

Product code: SUVTP10KH4B4S

Product name : SUVTP10KH4B4S

APC Smart-UPS VT 10kVA 400V w/4 Batt Mod, Start-Up 5X8, Int Maint Bypass, Parallel Capable

[APC SUVTP10KH4B4S uninterruptible power supply \(UPS\) 10 kVA 8000 W:](#)

APC Smart-UPS VT, 8000 Watts / 10 kVA, Input 400V 3PH / Output 230V, 400V 3PH, Interface Port DB-9 RS-232, Smart-Slot, Extended runtime model

Includes: Battery modules ship installed, Bolt down brackets, CD with software, Installation guide, Network Management Card, Power modules ship installed, Start up included, User Manual

Standard Lead Time: Usually Ships within 2 Weeks

APC SUVTP10KH4B4S. Output power capacity: 10 kVA, Output power: 8000 W, Input frequency: 40/70 Hz. Battery recharge time: 5 h. Product colour: Black. Weight: 599.1 kg, Package weight: 630 kg. Battery type: VRLA, Output connections: 1 x Hard Wire 4-wire (3PH + G) 1 x Hard Wire 5-wire (3PH + N + G) 1 x Screw Terminals, Input connection type: Hard Wire 5-wire (3PH + N + G)



Features		Operational conditions	
Output power capacity *	10 kVA	Storage relative humidity (H-H)	0 - 95%
Output power *	8000 W	Operating altitude	0 - 999.9 m
Input frequency *	40/70 Hz	Non-operating altitude	0 - 15000 m
Maximum current	14 A	Weight & dimensions	
Emergency Power Off (EPO)	✓	Weight	599.1 kg
Noise level	51.30 dB	Package weight	630 kg
Battery		Logistics data	
Battery recharge time	5 h	Harmonized System (HS) code	85078000
Replacement battery cartridge	4	Other features	
Design		Battery type	VRLA
Product colour *	Black	Output connections	1 x Hard Wire 4-wire (3PH + G) 1 x Hard Wire 5-wire (3PH + N + G) 1 x Screw Terminals
Operational conditions		Input connection type	Hard Wire 5-wire (3PH + N + G)
Operating temperature (T-T)	0 - 40 °C	Dimensions (WxDxH)	559 x 813 x 1499 mm
Storage temperature (T-T)	-50 - 40 °C	Output voltage note	380: 400 / 415 V
Operating relative humidity (H-H)	0 - 95%	Nominal input voltage	400 V
		Package dimensions (WxDxH)	650 x 1062 x 1643 mm



7313042570596

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-DEC-2024. Prints or copies of Information are only valid on the printed Publication date