



## APC Smart-UPS On-Line UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 15 kVA 12000 W 8 AC-pistorasia(a)

**Tuotemerkki :** APC

**Tuotekoodi:** SURT15KRMXLI

**Tuotteen nimi :** Smart-UPS On-Line

APC Smart-UPS On-Line. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 15 kVA, Lähtöteho: 12000 W. Pistorasian tyypit: C19 liitin, Virtapistoke: Pääte, Ulostulojen määrä: 8 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kapasiteetti: 3840 VAH, Tyypillinen varmuuskopioaika täydellä kuormituksella: 8,3 min. Kotelo: Telineasennettava/Torni, Tuotteen väri: musta, Telineen kapasiteetti: 12U. Tuotteen leveys: 432 mm, Tuotteen syvyys: 773 mm, Tuotteen korkeus: 533 mm



### Features

UPS topology *	Double-conversion (Online)
Output power capacity *	15 kVA
Output power *	12000 W
Waveform *	Sine
Input frequency *	40 - 70 Hz
Output operation voltage (min)	220 V
Output operation voltage (max)	240 V
Output frequency regulation	50/60 Hz
Maximum current	90 A
Number of output phases	1
Efficiency	95%
Crest factor	3:1
Emergency Power Off (EPO)	✓
Noise level	50 dB
Surge protection	✓
Audible alarm(s)	✓
Auto-restart	✓

### Ports & interfaces

AC outlet types	C19 coupler
Power plug	Terminal
AC outlets quantity	8 AC outlet(s)
Number of output IEC jumpers	2
Serial interface	✓
Serial interface type	RS-232
Cabling technology	10/100Base-T
SmartSlot	✓

### Battery

Cold start	✓
------------	---

### Design

Form factor *	Rackmount/Tower
Rack capacity	12U
Product colour *	Black
Display type	LCD
LED indicators	✓
Certification	EN/IEC 62040-2, EN/IEC 62040-1-1, VDE, PEP, EOL1

### Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m

### Technical details

Compliance certificates	RoHS
-------------------------	------

### Weight & dimensions

Width	432 mm
Depth	773 mm
Height	533 mm
Weight	247.7 kg
Package width	610 mm
Package depth	1003 mm
Package height	990 mm
Package weight	314.1 kg

Battery		Packaging data	
Battery technology	Sealed Lead Acid (VRLA)	Rack mount kit	✓
Battery capacity	3840 VAh	Cables included	RS-232
Typical backup time at full load	8.3 min	Manual	✓
Typical backup time at half load	22.3 min	Software CD	✓
Battery life (max)	5 year(s)	Logistics data	
Battery recharge time	2.5 h	Products per pallet	1 pc(s)
Hot-swap battery	✓	Harmonized System (HS) code	85078000
Automatic battery test	✓	Other features	
		Nominal output voltage	230 V
		Nominal input voltage	230 V



0731304255727



731304255727

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.