

APC Smart-UPS uninterruptible power supply (UPS) Line-Interactive 1 kVA 640 W 4 AC outlet(s)



Brand : APC

Product code: SUA1000RMI1U

Product name : Smart-UPS

Smart-UPS, 640 Watts, 1000 VA, Input 230V, Output 230V, Interface Port DB-9 RS-232, SmartSlot, USB, Rack Height 1 U

APC Smart-UPS. UPS topology: Line-Interactive, Output power capacity: 1 kVA, Output power: 640 W. AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: 4 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 216 VAh, Typical backup time at full load: 5.4 min. Form factor: Rackmount, Product colour: Black, Rack capacity: 1U. Width: 432 mm, Depth: 660 mm, Height: 44 mm

Features		Design	
UPS topology * Output power capacity * Output power * Waveform * Input operation voltage (min) * Input operation voltage (max) * Input frequency * Surge energy rating Noise level Surge protection Audible alarm(s)	Line-Interactive 1 kVA 640 W Sine 151 V 302 V 50/60 Hz 480 J 55 dB ✓	Product colour * LED indicators Certification	Black Battery replacement C-tick, CE, EN 50091-1, EN 50091-2, GOST, VDE, PEP, EOLI
		Operational conditions	
		Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	0 - 40 °C -15 - 45 °C 0 - 95% 0 - 95% 0 - 3000 m 0 - 15000 m
Ports & interfaces		Technical details	
AC outlet types	C13 coupler	Compliance certificates	RoHS
Power plug AC outlets quantity Number of output IEC jumpers USB port Serial interface Serial interface type SmartSlot	C14 coupler 4 AC outlet(s) 2 • RS-232	Weight & dimensions	
		Width Depth Height Weight Package width Package depth	432 mm 660 mm 44 mm 21.8 kg 559 mm 775 mm
Battery		Package height	191 mm
Battery technology	Sealed Lead Acid (VRLA)	Package weight	25.4 kg
Battery capacity	216 VAh	Packaging data	
Typical backup time at full load Typical backup time at half load Battery life (max) Battery recharge time	5.4 min 14.5 min 6 year(s) 2 h	Rack mount kit Cables included Manual Software CD	✓ RS-232, USB cable ✓
Hot-swap battery Automatic battery test	v V	Logistics data	
Design		Products per pallet Harmonized System (HS) code	8 pc(s) 85078000
Form factor * Rack capacity	Rackmount 1U	Other features	
		Interface Input connection type Nominal output voltage Nominal input voltage	DB-9 RS-232, SmartSlot, USB IEC-320 C14 230 V 230 V





731304123897

0731304123897

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.