

TP-Link TL-SG1024 Hallitsematon Gigabit Ethernet (10/100/1000) 10 musta

Tuotemerkki : TP-Link

Tuotekoodi: TL-SG1024 V11

Tuotteen nimi : TL-SG1024

TP-Link TL-SG1024. Kytkin tyyppi: Hallitsematon. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 24. Täysin kaksipuolinen. MAC-osoitetaulukko: 8000 entries, Kytkentäkapasiteetti: 48 Gbit/s. Verkkostandardit: IEEE 802.3ab, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x. Telineasennus, Kotelo: 1U





Management features		Design	
Switch type *	Unmanaged	LED indicators	1
Quality of Service (QoS) support	✓	Power	
Ports & interfaces		Power source *	AC
Basic switching RJ-45 Ethernet ports quantity * Basic switching RJ-45 Ethernet ports type * Gigabit Ethernet (copper) ports	Gigabit Ethernet (10/100/1000)	Power supply included * AC input voltage AC input frequency Power consumption (max)	✓ 100 - 240 V 50 - 60 Hz 13.62 W
quantity	24	Other features	
Network		Connectivity technology	Wired
Networking standards *	IEEE 802.3ab, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x	Bandwidth Connectivity LEDs	48 Gbit/s ✔
10G support * Copper ethernet cabling technology	× 1000BASE-T, 100BASE-TX, 10BASE-	Dimensions (W x D x H) (imperial)	439.4 x 180.3 x 43.2 mm (17.3 x 7.1 x 1.7")
	Т	Operational conditions	
Full duplex Half duplex Flow control support Auto MDI/MDI-X Auto-negotiation		Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating temperature (T-T)	0 - 40 °C -40 - 70 °C 10 - 90% 5 - 90% 32 - 104 °F
Data transmission		Heat dissipation	46.44 BTU/h
Supported data transfer rates Switching capacity * Forwarding rate MAC address table *	10/100/1000 Mbps 48 Gbit/s 35.7 Mpps 8000 entries	Weight & dimensions Width Depth Height	440 mm 180 mm 44 mm
Store-and-forward	1	Packaging content	
Maximum data transfer rate Jumbo frames support Jumbo frames	1 Gbit/s ✓ 10000	Cables included User guide Rack mount kit	AC ✓
Protocols		Packaging data	
Supported network protocols	CSMA/CD, TCP/IP	Package width Package depth	250 mm 528 mm

Design		Packaging data	
Rack mounting * Form factor	✓ 1U	Package height Package weight	80 mm 2.13 kg
Product colour	Black	Certificates	
		Certification	FCC, CE, RoHS







Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.