

TP-Link TL-MR6400 langaton reititin Nopea Ethernet Yksi kaista (2,4 GHz) 4G musta

Tuotemerkki : TP-Link

Tuotekoodi: TL-MR6400 V4

Tuotteen nimi : TL-MR6400

TP-Link TL-MR6400. WAN -liitintyyppi: RJ-45. Wi-Fi-taajuus: Yksi kaista (2,4 GHz), Wi-Fi-standardi: Wi-Fi 4 (802.11n), WLAN-tiedonsiirtonopeus (maks.): 300 Mbit/s. Ethernet LAN -käyttöliittymän tyyppi: Nopea Ethernet, Ethernet LAN -datanopeudet: 10,100 Mbit/s, Kaapelitekniikka: 10/100Base-T(X). Mobiiliverkon sukupolvi: 4G, 2G standardit: Edge, GPRS, GSM, 3G-standardit: HSPA+, UMTS. Tietoturva-algoritmit: 64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK, Palomuurisuojaus: DoS, SPI Firewall, IP and MAC Address Binding





WAN connection		Protocols	
Ethernet WAN *	✓	DHCP client	1
DSL WAN *	×	DHCP server	1
SIM card slot *	 Image: A set of the set of the	Universal Plug and Play (UPnP)	1
3G/4G USB modem compatibility *	×	Supported network protocols	IPv4, IPv6
WAN connection type	RJ-45	Design	
Wireless LAN features		Product colour	Black
Wi-Fi band *	Single-band (2.4 GHz)	Indication light	1
Top Wi-Fi standard *	Wi-Fi 4 (802.11n)	LED indicators	1
WLAN data transfer rate (max) *	300 Mbit/s	On/off switch	1
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)	Product type *	Tabletop router
Network		Certificates	
Ethernet LAN *	 Image: A set of the set of the	Certification	CE, FCC, RoHS
Ethernet LAN interface type *	Fast Ethernet	Packaging content	
Ethernet LAN data rates Cabling technology	10,100 Mbit/s 10/100Base-T(X)	Cables included	LAN (RJ-45)
5 57	IEEE 802.11b, IEEE 802.11g, IEEE	AC adapter included	1
Networking standards	802.11n, IEEE 802.3, IEEE 802.3u	Quick installation guide	1
Port forwarding	 Image: A set of the set of the	Quick start guide	1
Port triggering	 Image: A set of the set of the	Antenna	
Dynamic DNS (DDNS)	 Image: A set of the set of the	Antenna design *	Internal & external
Number of guest networks (2.4 GHz)	1	Antennas quantity	4
VPN server	PPTP VPN, IPSec VPN , OpenVPN	Detachable antenna(s)	1
VPN Passthrough	 Image: A set of the set of the	Power	
VPN support	PPTP, L2TP, IPSec	Power source type *	DC
Mobile network		Output voltage	12 V
Mobile network generation	4G	Output current	1 A
3G	✓	Operational conditions	
4G	✓	Operating temperature (T-T)	0 - 40 °C
2G standards	Edge, GPRS, GSM	Storage temperature (T-T)	-40 - 70 °C

Publication date: 24-APR-2025. Prints or copies of Information are only valid on the printed Publication date

Mobile network		Operational conditions	
3G standards HSI	HSPA+, UMTS LTE 850,900,1800,1900 MHz	Operating relative humidity (H-H)	10 - 90%
4G standard		Storage relative humidity (H-H)	5 - 90%
GSM bands supported		System requirements	
UMTS bands supported 4G bands supported	900,2100 MHz 800,900,1800,1900 MHz		Windows 10, Windows 7, Windows
Ports & interfaces	800,900,1800,1900 MHz	Windows operating systems supported	8, Windows 8.1, Windows 98SE, Windows NT, Windows Vista, Windows XP
Ethernet LAN (RJ-45) ports *	4	Linux operating systems supported	
USB port *	×	Mac operating systems supported	macOS
Memory card slot(s)	×	1 5 7 11	inacos
DC-in jack	1	Weight & dimensions	
Management features		Width	202 mm
-		Depth Height	141 mm 33.5 mm
Web-based management		5	55.5 11111
Wi-Fi Multimedia (WMM)/(WME)	 Image: A set of the set of the	Packaging data	
Quality of Service (QoS) support	1	Package width	307 mm
Reset button	J	Package depth	223 mm
WPS push button	✓	Package height Package weight	70 mm 600 g
Security			600 g
Security algorithms	64-bit WEP, 128-bit WEP, WPA,	Logistics data	
, <u>,</u>	WPA-PSK, WPA2, WPA2-PSK	Harmonized System (HS) code	85176990
Firewall		Other features	
Firewall security	DoS, SPI Firewall, IP and MAC Address Binding	Mobile network connection	1
Guest access	 Image: A start of the start of	WLAN data transfer rates supported	
Access Control List (ACL)	1	Bandwidth (first)	2.4 GHz
Stateful Packet Inspection (SPI)	1	Supported WAN type	RJ-45 SIM 2.4 GHz
DoS attack prevention	Image: A start of the start	Frequency band Rack mounting	2.4 GHZ
Parental control	1	xDSL connection	
DMZ support	1		×
Network address translation (NAT)	·		
	-		









Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.