



ATEN VE901-AT-G AV-signaalin jatkaja AV-lähetin ja -vastaanotin
musta

Tuotemerkki : ATEN

Tuotekoodi: VE901-AT-G

Tuotteen nimi : VE901-AT-G



ATEN VE901-AT-G. Malli: AV-lähetin ja -vastaanotin, Enimmäiserottelutarkkuus: 4096 x 2160 pikseliä, Tuetut kaapelityypit: Cat5e, Cat6, Cat6a. Yhteysteknologia: Langallinen. Käyttöjännite (lähetin): 5 V, Käyttöjännite (vastaanotin): 5 V, Tehonkulutus (TX): 2,84 W. Paino: 750 g, Vastaanottimen mitat (L x S x K): 94,2 x 66 x 29 mm, Vastaanottimen paino: 270 g. Pakkauksen leveys: 59 mm, Pakkauksen syvyys: 239 mm, Pakkauksen korkeus: 160 mm

Features		Operational conditions	
Type *	AV transmitter & receiver	Operating temperature (T-T)	0 - 40 °C
Maximum resolution *	4096 x 2160 pixels	Storage temperature (T-T)	-20 - 60 °C
Cable types supported	Cat5e, Cat6, Cat6a	Operating relative humidity (H-H)	0 - 80%
Maximum transfer distance	70 m	Storage relative humidity (H-H)	0 - 80%
LED indicators	✓	Weight & dimensions	
Supported video modes	1080p	Weight	750 g
Supported graphics resolutions	3840 x 2160, 4096 x 2160	Receiver dimensions (WxDxH)	94.2 x 66 x 29 mm
Bandwidth	10.2 Gbit/s	Receiver weight	270 g
Bandwidth	297 MHz	Transmitter dimensions (WxDxH)	94.2 x 66 x 29 mm
HDCP	✓	Transmitter weight	240 g
Material	Metal	Packaging data	
Rack mounting	✓	Package width	59 mm
Plug and Play	✓	Package depth	239 mm
Impedance	100 Ω	Package height	160 mm
HDCP version	1.4	Package weight	855 g
Product colour	Black	Packaging content	
HDBaseT certified	✓	AC adapter included	✓
Ports & interfaces		Manual	✓
Connectivity technology *	Wired	Logistics data	
RJ-45 input ports	1	Master (outer) case width	250 mm
RJ-45 output ports	1	Master (outer) case length	325 mm
HDBaseT port	✓	Master (outer) case height	175 mm
DisplayPorts in	1	Master (outer) case gross weight	4.85 kg
DisplayPorts out	1	Master (outer) case net weight	3.75 kg
DC-in jack	✓	Products per master (outer) case	5 pc(s)
Power			
Operating voltage (transmitter)	5 V		
Operating voltage (receiver)	5 V		
Power consumption (TX)	2.84 W		
Power consumption (RX)	5.72 W		



4719264645204

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-APR-2025. Prints or copies of Information are only valid on the printed Publication date