

APC SMX750INC UPS-virtalähde Linjainteraktiivinen 0,75 kVA 600 W 10 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: SMX750INC

Tuotteen nimi : SMX750INC

APC SMX750INC. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 0,75 kVA, Lähtöteho: 600 W. Pistorasian tyypit: C13 liitin, IEC Jumpers, Virtapistoke: C14 liitin, Ulostulojen määrä: 10 ACpistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun kestoikä (maks.): 5 vuosi/vuosia, Akun latausaika: 3 h. Kotelo: Telineasennettava/Torni, Tuotteen väri: musta, Telineen kapasiteetti: 2U. Sertifiointi: CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE, REACH






Features		Battery	
UPS topology *	Line-Interactive	Automatic battery test	 Image: A second s
Output power capacity *	0.75 kVA	Cold start	 Image: A set of the set of the
Output power *	600 W	Design	
Waveform * Input operation voltage (min) *	Pure sine 151 V	Form factor *	Rackmount/Tower
Input operation voltage (max) *	302 V	Rack capacity	20
Input frequency *	50/60 Hz	Product colour *	Black
Output operation voltage (min)	220 V	Display type	LED
Output operation voltage (max)	240 V	LED indicators	1
Output frequency	50/60 Hz	Operational conditions	
Surge energy rating	645 J	•	0 40.90
Emergency Power Off (EPO)	v -	Operating temperature (T-T)	0 - 40 °C -15 - 45 °C
Noise level	40 dB	Storage temperature (T-T) Operating relative humidity (H-H)	-15 - 45 °C 0 - 95%
Surge protection	1	Storage relative humidity (H-H)	0 - 95%
Audible alarm(s)	1	Operating altitude	0 - 3000 m
Web-based management	1	Non-operating altitude	0 - 15000 m
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm		
Auto-restart	1	Certification	CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE, REACH
Temperature voltage compensation	. ✓	Packaging content	
Ports & interfaces		Rack mount kit	1
AC outlet types	C13 coupler, IEC Jumpers	Cables included	RS-232, USB cable
Power plug	C14 coupler	Quick installation guide	1
AC outlets quantity	10 AC outlet(s)	Weight & dimensions	
USB port	✓	Width	432 mm
USB 2.0 ports quantity	1	Depth	432 mm 490 mm
Serial interface	✓	Height	490 mm
Serial interface type	RJ-45	Weight	22 kg
Serial ports quantity	1	-	22 Ng
Ethernet LAN (RJ-45) ports	1	Packaging data	
Cabling technology	10/100Base-T	Resource CD	✓
SmartSlot	1	Software CD	 Image: A start of the start of
Battery		Package width	589 mm
Battery technology	Sealed Lead Acid (VRLA)	Package depth	620 mm
		Package height	246 mm

Battery

Battery life (max) Battery recharge time Hot-swap battery 5 year(s) 3 h 🗸

Packaging data	
Package weight	26.4 kg
Logistics data	
Products per pallet	8 pc(s)
Harmonized System (HS) code	85078000
Total carbon footprint (kg of CO2e)	578.01





731304327745

0731304327745

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.