



Canon CanoScan LiDE 400 flatbed scanner, Black

Brand : Canon

Product family: CanoScan

Product code: 2996C010

Product name : CanoScan LiDE
400 flatbed scanner, Black




CanoScan LiDE 400 flatbed scanner, Black

[Canon CanoScan LiDE 400 flatbed scanner, Black:](#)

Enjoy a faster and smoother scanning experience in a lightweight, sleek package. With advanced image processing suited to the modern home and office, CanoScan LiDE 400's sophisticated design saves you space, time and power while expertly producing fast, high-resolution scans. Free your desk space with the option of vertical scanning and effortlessly copy bulky reports, photos or files with high-speed plug-and-scan USB connectivity and 5 one-touch EZ buttons.

Canon CanoScan LiDE 400 flatbed scanner, Black. Maximum scan size: 216 x 297 mm, Optical scanning resolution: 4800 x 4800 DPI, Input colour depth: 48 bit. Scanner type: Flatbed scanner, Product colour: Black. Sensor type: CIS, Light source: RGB LED. Maximum ISO A-series paper size: A4, ISO A-series sizes (A0...A9): A4. USB connector type: USB Type-C, Standard interfaces: USB

Scanning		Ports & interfaces	
Maximum scan size *	216 x 297 mm	Standard interfaces	USB
Optical scanning resolution *	4800 x 4800 DPI	Power	
Colour scanning	✓	Power supply type *	USB
Input colour depth	48 bit	Power consumption (typical)	4.5 W
Output colour depth	48 bit	Power consumption (standby)	0.3 W
Input greyscale depth	16 bit	Weight & dimensions	
Output greyscale depth	8 bit	Width	250 mm
Design		Depth	367 mm
Scanner type *	Flatbed scanner	Height	42 mm
Product colour *	Black	Weight	1.7 kg
Built-in display *	✗	Packaging content	
Performance		Bundled software	Scan Gear for Win Scan Utility for Win
Sensor type *	CIS	System requirements	
Light source	RGB LED	Windows operating systems supported	✓
Paper handling		Mac operating systems supported	✓
Maximum ISO A-series paper size *	A4	Operational conditions	
ISO A-series sizes (A0...A9)	A4	Operating temperature (T-T)	5 - 35 °C
Letter	✓	Operating relative humidity (H-H)	10 - 90%
Ports & interfaces		Logistics data	
USB port *	✓	Harmonized System (HS) code	84716070
USB connector type	USB Type-C		



4549292119855

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-FEB-2025. Prints or copies of Information are only valid on the printed Publication date