



ATEN VM0808HB-AT-G matriisikytkin AV-matriisikytkin Sisäänrakennettu näyttö 38,1 W

Tuotemerkki : ATEN

Tuotekoodi: VM0808HB-AT-G

Tuotteen nimi : VM0808HB-AT-G

ATEN VM0808HB-AT-G. Tuotetyyppi: AV-matriisikytkin, Tiedonsiirtonopeus: 18 Gbit/s, Maksimaalinen pikselikello: 600 MHz. Kotelon väri: musta, Kotelon materiaali: Metalli, Telineen kapasiteetti: 1U. Tehonkulutus (maks.): 38,1 W, Virrankulutus: 37,8 W, AC-syöttöjännite: 100-240 V. Määrä per tuotepakkaus: 1 kpl, Tuotepakkauksen paino: 5,63 kg, Tuotepakkauksen pituus: 515 mm. Tuotteen leveys: 432,4 mm, Tuotteen syvyys: 262,3 mm, Tuotteen korkeus: 44 mm



Features		Power	
Product type *	AV matrix switcher	Input current	1 A
Data transfer rate	18 Gbit/s	Operational conditions	
Maximum pixel clock	600 MHz	Operating temperature (T-T)	0 - 40 °C
Maximum resolution	4096 x 2160 pixels	Storage temperature (T-T)	-20 - 60 °C
HDCP	✓	Operating relative humidity (H-H)	0 - 80%
HDCP version	2.2	Storage relative humidity (H-H)	0 - 80%
3D	✓	Heat dissipation	177 BTU/h
High Dynamic Range (HDR) supported	✓	Heat dissipation (max)	179 BTU/h
Extended display identification data (EDID)	✓	Logistics data	
Supported resolutions	4096 x 2160, 3840 x 2160, 1920 x 1200	Products per master (outer) case	1 pc(s)
Design		Master (outer) case gross weight	5.63 kg
Housing colour	Black	Master (outer) case length	515 mm
Housing material	Metal	Master (outer) case width	338 mm
Rack mounting	✓	Master (outer) case height	155 mm
Rack capacity	1U	Master (outer) case net weight	4.15 kg
Control type	Buttons	Harmonized System (HS) code	85299097
On/off switch	✓	Weight & dimensions	
LED indicators	✓	Width	432.4 mm
Remote control included	✓	Depth	262.3 mm
Display		Height	44 mm
Built-in display *	✓	Weight	4.15 kg
Ports & interfaces		Package width	338 mm
HDMI input ports quantity	8	Package depth	515 mm
HDMI output ports quantity	8	Package height	155 mm
Ethernet LAN (RJ-45) ports	1	Package weight	5.63 kg
RS-232 ports	1	Packaging content	
Remote (IR) input	1	Cables included	AC
Power		Rack mount kit	✓
Power consumption (max) *	38.1 W	Quick start guide	✓
Power consumption (typical)	37.8 W	IR receiver included	✓

Power

AC input voltage	100-240 V
AC input frequency	50-60 Hz



4719264646836

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-APR-2025. Prints or copies of Information are only valid on the printed Publication date