

Epson TM-H6000V-234 180 x 180 DPI Wired & Wireless Dot matrix POS printer

Brand : Epson

Product code: C31CG62234

Product name : TM-H6000V-234



- Integrated point-of-sale printer: Capable of receipt printing, slip printing and cheque processing
- Boost efficiency: Fast prints speeds up to 350mm/s¹, cheque processing and auto-cutter
- Flexible connectivity: Built-in USB and Ethernet in all models
- An investment for the future: ePOS-Print, ePOS-display and NFC
- Great value: Low total cost of ownership

180 x 180DPI, 350mm/sec, NFC, USB 1.1, USB 2.0, Ethernet, Serial, Black

Epson TM-H6000V-234. Print technology: Dot matrix, Type: POS printer, Maximum resolution: 180 x 180 DPI. Maximum roll diameter: 8.3 cm, Supported paper width: 80 mm, Maximum paper size (slip): 230 x 297 mm. Connectivity technology: Wired & Wireless, USB connector: USB Type-A / USB Type-B, Serial interface type: RS-232. Sound pressure level (printing): 55 dB, Sound pressure level (standby): 55 dB, Mean time between failures (MTBF): 180000 h. Product colour: Black

| Printing | | Features | |
|-----------------------------------|---|-----------------------------------|---|
| Colour | ✗ | Certification | CE, EN55024, EN55032 Class A, IEC61000-4-2, IEC61000-4-3, IEC61000-4-4, IEC61000-4-5, IEC61000-4-6, IEC61000-4-11, Directive 2014/30/EU |
| Maximum resolution | 180 x 180 DPI | | |
| Print speed | 5.7 lps | Design | |
| Print speed | 350 mm/sec | Product colour * | Black |
| Print speed (receipt) | 350 mm/sec | Power | |
| Character size | 1.24 x 3.11 mm | AC input voltage | 24 V |
| Character density | 17.8 cpi | Operational conditions | |
| Printing characters | Text, Graphic, Barcode | Operating temperature (T-T) | 5 - 45 °C |
| Character sets | ANK | Storage temperature (T-T) | -10 - 50 °C |
| Print technology * | Dot matrix | Operating relative humidity (H-H) | 10 - 90% |
| Type * | POS printer | Storage relative humidity (H-H) | 10 - 90% |
| Paper handling | | System requirements | |
| Maximum roll diameter | 8.3 cm | Pre-installed software | Server Direct Print, ePOS-Display, ePOS-Print |
| Supported paper width | 80 mm | Weight & dimensions | |
| Maximum paper size (slip) | 230 x 297 mm | Width | 186 mm |
| Ports & interfaces | | Depth | 278 mm |
| USB port * | ✓ | Height | 181 mm |
| USB connector | USB Type-A / USB Type-B | Weight | 4.4 kg |
| Serial interface * | ✓ | Packaging data | |
| Serial interface type | RS-232 | Quantity per pack | 1 pc(s) |
| Connectivity technology * | Wired & Wireless | Package width | 295 mm |
| Near Field Communication (NFC) | ✓ | Package depth | 382 mm |
| Standard interfaces | Ethernet, NFC, RS-232, USB 1.1, USB 2.0 | Package height | 285 mm |
| Network | | Package weight | 5.83 kg |
| Ethernet LAN * | ✓ | Packaging content | |
| Features | | AC adapter included | ✓ |
| Sound pressure level (printing) | 55 dB | Print technology | |
| Sound pressure level (standby) | 55 dB | Column capacity | 45 cps / 60 cps |
| Mean time between failures (MTBF) | 180000 h | | |
| Cutter | ✓ | | |
| Half-cutter | ✓ | | |
| Autocutter durability | 3 million cuts | | |

| Features | | Logistics data | |
|--|---|--|------------------------------|
| Built-in MICR | ✓ | Pallet weight (UK) | 0 g |
| Paper save function | ✓ | Harmonized System (HS) code | 84433210 |
| Print head life | 200 km | Products per pallet | 56 pc(s) |
| Country of origin | China | Products per pallet layer | 8 pc(s) |
| Maximum number of copies (endorsement) | 2 copies | Pallet gross width | 80 cm |
| Maximum number of copies (slip) | 3 copies | Pallet gross length | 120 cm |
| Printer receipt unit life | 20000000 lines | Pallet gross height | 2.18 m |
| Printer slip unit life | 27000000 lines | Pallet gross weight | 0 g |
| Ribbon life (endorsement) | 3 million characters | Products per pallet (UK) | 70 pc(s) |
| Ribbon life (slip) | 4 million characters | Products per pallet layer (UK) | 10 pc(s) |
| Built-in sensors details | Middle of Paper pass sensor, Front cover open sensor, Roll paper cover open sensor, Paper End Sensor, Top of Form sensor, Bottom of Form sensor, Slip eject sensor, Receipt near-end sensor | Pallet width (UK) | 100 cm |
| | | Pallet length (UK) | 120 cm |
| | | Pallet height (UK) | 2.18 m |
| | | Technical details | |
| Font size | | endorsement: 1.09 mm (W) x 2.41 mm (H) | |
| Changeable interface | ✓ | | |
| Other features | | Buffer size | 4 KB |
| | | Mean cycles between failures (MCBF) | 65000000 |
| | | Print head life | 200000000 million characters |



8715946651170

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-FEB-2025. Prints or copies of Information are only valid on the printed Publication date