

## D-Link DIS-200G-12S verkkokytkin Hallittu L2 Gigabit Ethernet (10/100/1000) musta

**Tuotemerkki** : D-Link

**Tuotekoodi**: DIS-200G-12S


**Tuotteen nimi** : DIS-200G-12S

D-Link DIS-200G-12S. Kytkin tyyppi: Hallittu, Kytinkerros: L2. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 10, Console-portti: RJ-45. Täysin kaksipuolinen. MAC-osoitetaulukko: 8000 entries, Kytkentäkapasiteetti: 24 Gbit/s. Verkkostandardit: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE.... DC-syöttöjännite: 12 - 48 V. Seinäkiinnitteinen, Telineasennus



Management features		Design	
Switch type *	Managed	International Protection (IP) code	IP30
Switch layer	L2	Wall mountable	✓
Quality of Service (QoS) support	✓	DIN rail mounting	✓
Web-based management	✓	Number of fans	0 fan(s)
Configuring Location Settings (CLI)	✓	Safety	UL60950-1
System event log	✓	Electromagnetic compatibility	CISPR 22, FCC Part 15B Class A
Ports & interfaces		Performance	
Basic switching RJ-45 Ethernet ports quantity *	10	Mean time between failures (MTBF)	276773 h
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power	
Gigabit Ethernet (copper) ports quantity	10	DC input voltage	12 - 48 V
SFP module slots quantity	2	Power consumption (max)	10.26 W
Console port	RJ-45	Power over Ethernet (PoE)	
Network		Power over Ethernet (PoE) *	✗
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Operational conditions	
		Operating temperature (T-T)	-40 - 65 °C
10G support *	✗	Storage temperature (T-T)	-40 - 85 °C
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T	Operating relative humidity (H-H)	0 - 95%
Port mirroring	✓	Storage relative humidity (H-H)	0 - 95%
Full duplex	✓	Heat dissipation	35.01 BTU/h
Flow control support	✓	Weight & dimensions	
Link aggregation	✓	Width	171.2 mm
Broadcast storm control	✓	Depth	48 mm
Auto MDI/MDI-X	✓	Height	210 mm
Spanning tree protocol	✓	Weight	1.63 kg
		Packaging data	
		Package width	217 mm
		Package depth	355 mm
		Package height	76 mm
		Package weight	2.07 kg

Network		Technical details	
Auto-negotiation	✓	Shipping (inner) case height	25.2 cm
Active link detection	✓	Shipping (inner) case width	37.2 cm
VLAN support	✓	Shipping (inner) case length	40.9 cm
Virtual LAN features	Voice VLAN, Tagged VLAN, Port-based VLAN	Shipping (inner) case net weight	10.4 kg
Number of VLANs	4094	Products per shipping (inner) case	5 pc(s)
Optical fiber		Pallet gross weight (air)	268.8 kg
Fiber ethernet cabling technology	1000BASE-X	Master (outer) cases per pallet (air)	24 pc(s)
Data transmission		Products per pallet (air)	120 pc(s)
Switching capacity *	24 Gbit/s	Pallet gross length	110 cm
Forwarding rate	17.85 Mpps	Pallet gross width	120 cm
MAC address table *	8000 entries	Pallet height (air)	114.3 cm
Store-and-forward	✓	Pallet gross weight (sea)	470.4 kg
Jumbo frames support	✓	Master (outer) cases per pallet (sea)	42 pc(s)
Jumbo frames	9216	Products per pallet (sea)	210 pc(s)
Security		Pallet height (sea)	189.9 cm
DHCP features	DHCP client	Shipping (inner) case gross weight	11.2 kg
IGMP snooping	✓	Certificates	
Security algorithms	802.1x RADIUS, SSL/TLS	Certification	CE, FCC, BSMI EN 61000-4-2 ESD EN 61000-4-3 RS EN 61000-4-4 EFT EN 61000-4-5 EN 61000-4-6 CS EN 61000-4-8 IEC 60068-2-27 IEC 60068-2-32 IEC 60068-2-6
Authentication	Port-based authentication	Logistics data	
DoS attack prevention	✓	Harmonized System (HS) code	85176990
Authentication type	RADIUS		
Queue scheduling algorithms	SPQ, Weighted Round Robin (WRR)		
Multicast features			
Multicast support	✓		
Protocols			
Management protocols	SNMP v1/v2c/v3, SNMP, Telnet		
Design			
Rack mounting *	✓		
Product colour	Black		
Housing material	Metal		
LED indicators	✓		



0790069433535



790069433535

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.